

Factory-Verified Replacement

MERYDOM 91-20 0741/1-07143

Certified for interchange with IMO 91-20 0741/1-07143.
This document consolidates the public product record,
complete published specifications, technical media,
source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle,
mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

91-20 0741/1-07143

REFERENCE

IMO 91-20 0741/1-07143

SERIES

920 Series

STRUCTURE

Cuscinetto a sfere con anelli
flangiati

OVERALL OD

838.8 mm

OVERALL ID

635 mm


OVERALL HEIGHT

mm

GEAR

Dentatura esterna

Published Technical Drawing



imo-91200741107143-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	91-20 0741/1-07143
Certified interchangeable with	IMO 91-20 0741/1-07143
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	FNVHLKLWYQPSBZFWFZVQHJPLQY
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	IMO
Reference series	920 Series
Reference model	91-20 0741/1-07143
Bearing structure	Cuscinetto a sfere con anelli flangiati
Gear arrangement	Dentatura esterna
DIMENSION	
Overall outside diameter (Da)	838,8 mm
Overall inside diameter (di)	635 mm
Assembly weight (G)	56 kg

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MOUNTING	
Outer ring bolt circle (La)	785 mm
Outer ring mounting-hole count (na)	18
Inner ring bolt circle (Li)	662 mm
Inner ring mounting-hole count (ni)	16
GEAR	
Gear pitch diameter (d)	828 mm
Gear module (m)	6 mm
Gear tooth count (z)	138
PERFORMANCE	
Permitted circumferential force, normal (fz_norm)	17,5 kN
Permitted circumferential force, maximum (fz_max)	32,7 kN
Static radial load rating (Co_rad)	212 kN
Static axial load rating (Co_ax)	496 kN
Dynamic radial load rating (C_rad)	194 kN
Dynamic axial load rating (C_ax)	195 kN
PERFORMANCE RATINGS	
Fz Norm	17,5 kN Not simultaneous with other listed dynamic ratings
Fz Max	32,7 kN Not simultaneous with other listed dynamic ratings
Co Rad	212 kN Not simultaneous with other listed dynamic ratings
Co Ax	496 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
C Rad	194 kN Not simultaneous with other listed dynamic ratings
C Ax	195 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	18 holes - See source drawing
Inner ring mounting	16 holes - See source drawing
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	138
SOURCE TRACEABILITY	
Source document code	IMO_FLANGE_BALL_EN
Source file	imo_kugeldrehverbindung_mit_flanschring-en.pdf
PDF page	5
Printed page	Not published
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	imo-91200741107143-curve.webp SHA-256: 19d2fe2a291fdbbc2526400e39b60e5ffe7a0367df12ae58e259f81caa4d5966f
Outline Drawing	imo-91200741107143-drawing.webp SHA-256: 9994aab92535c0bbe186166cc3049e209de39ef1dbfdd1df8785e382810a2749

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Bearing ring material: C45N
4 Taper type grease nipples on the circumference
Mounting holes equally spaced
Raceway system supplied pre-lubricated
Dimensions without tolerances DIN ISO 2768 coarse

Clearance of precision version

Position	Radial Clearance	Axial Clearance
1	max. 0.03	max. 0.03
2	max. 0.03	max. 0.03
3	max. 0.03	max. 0.03
4	max. 0.04	max. 0.04
5	max. 0.04	max. 0.04
6	max. 0.05	max. 0.05
7	max. 0.05	max. 0.05
8	max. 0.06	max. 0.06

imo-91200741107143-curve.webp | SHA-256: 19d2fe2a291fdb2526400e39b60e5ffe7a0367df12ae58e259f81caa4d5966f

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

FNVHLKLWYQPSBZFWFZVQHJPLQY

SOURCE DOCUMENT

IMO_FLANGE_BALL_EN

SOURCE FILE

**imo_kugeldrehverbindung_mit_flansch-
ing-en.pdf**

SOURCE LOCATION

**PDF page 5 | Printed page Not
published**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/imo/91-20-0741-1-07143/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.