

Factory-Verified Replacement

MERYDOM 16275001

Certified for interchange with Kaydon 16275001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16275001

REFERENCE

Kaydon 16275001

SERIES

DT Series

STRUCTURE

Sfere a contatto su otto punti

OVERALL OD

1,676.4 mm

OVERALL ID

1,209.04 mm

OVERALL HEIGHT

203.2 mm

GEAR

Dentatura interna

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16275001
Certified interchangeable with	Kaydon 16275001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	P66DRYH6A4WUXYLMTH3UVJWYD
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	DT Series
Reference model	16275001
Bearing structure	Sfere a contatto su otto punti
Gear arrangement	Dentatura interna
DIMENSION	
Overall outside diameter (Do)	66.000 in Metric reference: circa 1.676 mm
Overall inside diameter (di)	47.600 in Metric reference: circa 1.209 mm
Inner ring body ID (dr)	50.125 in Metric reference: circa 1.273,18 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	8.000 in Metric reference: circa 203 mm
Assembly weight (G)	2820 lb Metric reference: circa 1.279,13 kg
MOUNTING	
Outer ring bolt circle (Lo)	63.000 in Metric reference: circa 1.600 mm
Inner ring bolt circle (Li)	53.000 in Metric reference: circa 1.346 mm
GEAR	
Gear pitch diameter (D2)	48.667 in Metric reference: circa 1.236,14 mm
Diametral pitch (Pd)	1,5
Gear tooth count (z2)	73
PERFORMANCE	
Maximum gear tooth load (Fz)	78680 lbf Metric reference: circa 349,99 kN
Moment load rating (Crm)	3921100 ft lbf Metric reference: circa 5.316,3 kN m
PERFORMANCE RATINGS	
Moment	3921100.0000000000 ft lbf Metric reference: circa 5.316,3 kN m
Gear Tooth	78680.0000000000 lbf Metric reference: circa 349,99 kN
MOUNTING INTERFACES	
Outer ring mounting	42 holes - 1.625
Inner ring mounting	45 holes - 1.625
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	1.5 DP

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Module reference	16.933333 mm
Number of teeth	73
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	90
Printed page	88
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID P66DRYH6A4WUXYLMTH3UVJWYD	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 90 Printed page 88
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/kaydon/16275001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.