

Factory-Verified Replacement

MERYDOM HS6-37P1Z

Certified for interchange with Kaydon HS6-37P1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

HS6-37P1Z

REFERENCE

Kaydon HS6-37P1Z

SERIES

HS Series

STRUCTURE

Sfere a quattro punti di contatto

OVERALL OD

1,047.75 mm

OVERALL ID

833.882 mm

OVERALL HEIGHT

55.88 mm

GEAR

Senza dentatura

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	HS6-37P1Z
Certified interchangeable with	Kaydon HS6-37P1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	JLU3KJJ6VQ2E5CDCAQ7BR47GTV
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	HS Series
Reference model	HS6-37P1Z
Bearing structure	Sfere a quattro punti di contatto
Gear arrangement	Senza dentatura
DIMENSION	
Overall outside diameter (Do)	41.250 in Metric reference: circa 1.047,8 mm
Overall inside diameter (di)	32.830 in Metric reference: circa 833,9 mm
Overall height (H)	2.200 in Metric reference: circa 56 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	233 lb Metric reference: circa 105,687 kg
MOUNTING	
Outer ring bolt circle (Lo)	39.750 in Metric reference: circa 1.009,7 mm
Inner ring bolt circle (Li)	34.380 in Metric reference: circa 873,3 mm
PERFORMANCE	
Moment load rating (Crm)	130900 ft lbf Metric reference: circa 177,48 kN m
PERFORMANCE RATINGS	
Moment	130900.0000000000 ft lbf Metric reference: circa 177,48 kN m
MOUNTING INTERFACES	
Outer ring mounting	18 holes - 0.688 through, equally spaced
Inner ring mounting	20 holes - 0.688 through, equally spaced
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	55
Printed page	53
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID JLU3KJJ6VQ2E5CDCAQ7BR47GTV	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 55 Printed page 53
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/kaydon/hs6-37p1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.