

Factory-Verified Replacement

MERYDOM RK6-29P1Z

Certified for interchange with Kaydon RK6-29P1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RK6-29P1Z

REFERENCE

Kaydon RK6-29P1Z

SERIES

RK Series

STRUCTURE

Sfere a quattro punti di contatto

OVERALL OD

848.106 mm

OVERALL ID

634.238 mm

OVERALL HEIGHT

56.007 mm

GEAR

Senza dentatura

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RK6-29P1Z
Certified interchangeable with	Kaydon RK6-29P1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	6W247MFYYMKDLRSLSELXGBDNI
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	RK Series
Reference model	RK6-29P1Z
Bearing structure	Sfere a quattro punti di contatto
Gear arrangement	Senza dentatura
DIMENSION	
Overall outside diameter (Do)	33.390 in Metric reference: circa 848,1 mm
Overall inside diameter (di)	24.970 in Metric reference: circa 634,2 mm
Outer ring body OD (Dr)	30.870 in Metric reference: circa 784,1 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Outer ring inner diameter (Di)	29.220 in Metric reference: circa 742,2 mm
Inner ring outer diameter (do)	29.140 in Metric reference: circa 740,2 mm
Inner ring body ID (dr)	27.490 in Metric reference: circa 698,2 mm
Overall height (H)	2.205 in Metric reference: circa 56,01 mm
Assembly weight (G)	104 lb Metric reference: circa 47,174 kg
MOUNTING	
Outer ring bolt circle (Lo)	32.250 in Metric reference: circa 819,2 mm
Inner ring bolt circle (Li)	26.130 in Metric reference: circa 663,7 mm
PERFORMANCE	
Moment load rating (Crm)	54200 ft lbf Metric reference: circa 73,49 kN m
PERFORMANCE RATINGS	
Moment	54200.0000000000 ft lbf Metric reference: circa 73,49 kN m
MOUNTING INTERFACES	
Outer ring mounting	15 holes - 0.688 through, equally spaced
Inner ring mounting	18 holes - 0.688 through, equally spaced
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	50

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Printed page	48
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID 6W247MFYYMKDLRSLSELXGBDNI	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 50 Printed page 48
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/kaydon/rk6-29p1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.