

Factory-Verified Replacement

MERYDOM V40E033

Certified for interchange with La Leonessa V40E033. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

V40E033

SERIES

1RE Series

OVERALL OD

2,027 mm

OVERALL HEIGHT

150 mm

REFERENCE

La Leonessa V40E033

STRUCTURE

Sfere a quattro punti di contatto


OVERALL ID

1,615 mm


GEAR

Dentatura esterna

Published Technical Drawing



la-leonessa-1re-drawing.webp



Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	V40E033
Certified interchangeable with	La Leonessa V40E033
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	W24MRYKBJU5GW5F52NTYYUEFKH
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	1RE Series
Reference model	V40E033
Bearing structure	Sfere a quattro punti di contatto
Gear arrangement	Dentatura esterna
DIMENSION	
Mass (P)	1.011 kg
Overall outside diameter (De)	2.027 mm
Overall inside diameter (Di)	1.615 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	150 mm
Dim Dr (Dr)	1.790,5 mm
Dim Centering External (Ce)	1.808 +0,4/0 mm
Dim Centering Internal (Ci)	1.617 +0,4/0 mm
MOUNTING	
Outer ring bolt circle (Ie)	1.895 mm
Outer ring mounting-hole count (ne)	48
Outer ring mounting-hole specification (Me)	M30
Inner ring bolt circle (Ii)	1.675 mm
Inner ring mounting-hole count (ni)	48-1
Inner ring mounting-hole specification (Mi)	M30
GEAR	
Gear module (m)	14 mm
Gear tooth count (z)	142
Addendum modification product x*m (xm)	7 mm
Liebherr catalogue gear dimension k*m (km)	1,5 mm
Gear pitch diameter (Dp)	2.002 mm
Gear Tooth Height (Hd)	130 mm
PERFORMANCE	
Basic static axial load rating (C0a)	10.360 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Static tilting moment rating (M0r)	4.277 kNm
Normal tooth force (Fnom)	235 kN
Maximum tooth force (Fmax)	470 kN
MISCELLANEOUS	
Pattern (Schema)	B
PERFORMANCE RATINGS	
Rating Axial Static	10.360 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	4.277 kNm Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	235 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	470 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - 48; M30
Inner ring mounting	48 holes - 48-1; M30
GEAR INTERFACE	
Pitch system	module
Module reference	14 mm
Number of teeth	142
SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017
Source file	SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
PDF page	12
Printed page	12
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-1re-static_load_curve.webp SHA-256: d7aae043a7185155fb61d59e50819f72c59987082f018cd5cc43cc5387066075
Outline Drawing	la-leonessa-1re-drawing.webp SHA-256: 9def12f376fbd9bc222f66ab0503412bd5a475fdfe624e4dbfe0ca549ea4d61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-1re-static_load_curve.webp | SHA-256:
d7aae043a7185155fb61d59e50819f72c59987082f018cd5cc43cc5387066075

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

W24MRYKBJU5GW5F52NTYYUEFKH

SOURCE FILE

SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017

SOURCE LOCATION

PDF page 12 | Printed page 12

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/la-leonessa/v40e033/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.