

Factory-Verified Replacement

MERYDOM ROD01876-050DA15-900-000

Certified for interchange with Liebherr ROD01876-050DA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

ROD01876-050DA15-900-000

REFERENCE

Liebherr ROD01876-050DA15-900-000

SERIES

ROD_50_DA Series

STRUCTURE

Rulli a tre file

OVERALL OD

2,232 mm

OVERALL ID

1,610 mm


OVERALL HEIGHT

322 mm

GEAR

Dentatura esterna

Published Technical Drawing



liebherr-page-132-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	ROD01876-050DA15-900-000
Certified interchangeable with	Liebherr ROD01876-050DA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	4VZETMUHM5OU7NRTIZT6MOXUF7
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	ROD_50_DA Series
Reference model	ROD01876-050DA15-900-000
Bearing structure	Rulli a tre file
Gear arrangement	Dentatura esterna
DIMENSION	
Mass (Weight)	3.180 kg
Overall outside diameter (Da)	2.232 mm
Overall inside diameter (Di)	1.610 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	322 mm
Liebherr catalogue dimension O (O)	1.950 mm
Liebherr catalogue dimension U (U)	1.925 mm
Liebherr catalogue dimension H1 (H1)	259 mm
Liebherr catalogue dimension H2 (H2)	273 mm
MOUNTING	
Outer ring bolt circle (La)	2.055 mm
Inner ring bolt circle (Li)	1.705 mm
La/Li mounting-hole count (n)	56
Mounting fastener specification (M)	42
Liebherr catalogue count n1 (n1)	8
GEAR	
Gear pitch diameter (d)	2.175 mm
Gear module (m)	15 mm
Gear tooth count (z)	145
Addendum modification product x^*m (x^*m)	15 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-1,5 mm
Gear face width (b)	259 mm
PERFORMANCE	
Standard tooth force (Fz standard)	338 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	676 kN
Static load rating (Cstat)	34.609 kN
Dynamic load rating (Cdyn)	4.980 kN
PERFORMANCE RATINGS	
Rating Dynamic	4.980 kN Not simultaneous with other listed dynamic ratings
Rating Static	34.609 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	676 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	338 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	56 holes - 42
Inner ring mounting	56 holes - 42
GEAR INTERFACE	
Pitch system	module
Module reference	15 mm
Number of teeth	145
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	132
Printed page	132


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-132-curve.webp SHA-256: 906a3c21fa0bff2f96b355718f27513d403736d28d06d9b1760d3421b2bf4bfd
Outline Drawing	liebherr-page-132-drawing.webp SHA-256: dce2e2500a3daa3838b8ca5cdd27994184301f3b96c333e0288bb3af5f2e59cb

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-132-curve.webp | SHA-256: 906a3c21fa0bff2f96b355718f27513d403736d28d06d9b1760d3421b2bf4bfd

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

4VZETMUHM5OU7NRTIZT6MOXUF7

SOURCE FILE

liebherr-slewing-bearings-product-ca
talogue-pt-metric-web.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA
TALOGUE-2018

SOURCE LOCATION

PDF page 132 | Printed page 132

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:
<https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/liebherr/rod01876-050da15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.