

MERYDOM 06-2810-09

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

Dentatura esterna

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	06-2810-09
Certified interchangeable with	ROLLIX 06-2810-09
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	46QXLV7F4QNHJRJOZSLUA7BLW5
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	06 Series
Reference model	06-2810-09
Bearing structure	Rulli incrociati a una corona
Gear arrangement	Dentatura esterna
DIMENSION	
Overall height (HT)	164 mm
Overall outside diameter (Dia De)	3.116 mm
Outer ring height (He)	148 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	2.600 mm
Inner ring height (Hi)	142 mm
Assembly weight (Weight)	2.208 kg
MOUNTING	
Outer ring pilot diameter (Dia Ce)	2.818 mm
Inner ring pilot diameter (Dia Ci)	2.607 mm
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	2.950 mm
Outer ring mounting-hole count (Ne)	80
Outer ring mounting-hole specification (Dhe)	33 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	2.670 mm
Inner ring mounting-hole count (Ni)	80
Inner ring mounting-hole specification (Dhi)	33 mm
GEAR	
Gear module (Module)	20 mm
Gear tooth count (Z)	152
Gear face width (W)	148 mm
PERFORMANCE	
Gear capacity, unhardened (Gear capacity unhardened)	584 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Gear capacity, hardened (Gear capacity hardened)	679 kN
MISCELLANEOUS	
Ring with greasing holes (Ring with greasing holes)	I
Greasing hole type (Greasing hole type)	R
PERFORMANCE RATINGS	
Rating Gear Capacity Hardened	679 kN Not simultaneous with other listed dynamic ratings
Rating Gear Capacity Unhardened	584 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	80 holes - External ring hole type Th; Dhe 33 mm
Inner ring mounting	80 holes - Inner ring hole type Th; Dhi 33 mm
GEAR INTERFACE	
Pitch system	module
Module reference	20 mm
Number of teeth	152
SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	103
Printed page	103
Source language	EN


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-103-curve.webp SHA-256: 11762ccf3814c0d7b985627797dc2ae88086c07b96639b1337131d1fb55cbf1a
Outline Drawing	rollix-page-103-drawing.webp SHA-256: a5736d9cad0fde539f2570119068ca06caaaaedd1bc75c37763ca7927829b61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-103-curve.webp | SHA-256: 11762ccf3814c0d7b985627797dc2ae88086c07b96639b1337131d1fb55cbf1a

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID 46QXLV7F4QNHJRJOZSLUA7BLW5	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 103 Printed page 103
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/rollix/06-2810-09/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.