

Factory-Verified Replacement

MERYDOM 74-1095-01

Certified for interchange with ROLLIX 74-1095-01. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

74-1095-01

SERIES

74 Series

OVERALL OD

1,216 mm

OVERALL HEIGHT

83 mm

REFERENCE

ROLLIX 74-1095-01

STRUCTURE

Cuscinetto a rulli a due corone


OVERALL ID

942 mm

GEAR

Dentatura interna

Published Technical Drawing



rollix-page-136-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	74-1095-01
Certified interchangeable with	ROLLIX 74-1095-01
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	26QNDMHP7VJYH2AVZSGOXZ3K53
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	74 Series
Reference model	74-1095-01
Bearing structure	Cuscinetto a rulli a due corone
Gear arrangement	Dentatura interna
DIMENSION	
Overall height (HT)	83 mm
Overall outside diameter (Dia De)	1.216 mm
Outer ring height (He)	75 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	942 mm
Inner ring height (Hi)	75 mm
Assembly weight (Weight)	211 kg
MOUNTING	
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	1.168 mm
Outer ring mounting-hole count (Ne)	66
Outer ring mounting-hole specification (Dhe)	22 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	1.032 mm
Inner ring mounting-hole count (Ni)	66
Inner ring mounting-hole specification (Dhi)	22 mm
GEAR	
Gear module (Module)	10 mm
Gear tooth count (Z)	95
Gear face width (W)	65 mm
PERFORMANCE	
Gear capacity, unhardened (Gear capacity unhardened)	124 kN
Gear capacity, hardened (Gear capacity hardened)	144 kN
MISCELLANEOUS	

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MISCELLANEOUS (CONTINUED)	
Ring with greasing holes (Ring with greasing holes)	E
Greasing hole type (Greasing hole type)	R
PERFORMANCE RATINGS	
Rating Gear Capacity Hardened	144 kN Not simultaneous with other listed dynamic ratings
Rating Gear Capacity Unhardened	124 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	66 holes - External ring hole type Th; Dhe 22 mm
Inner ring mounting	66 holes - Inner ring hole type Th; Dhi 22 mm
GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	95
SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	136
Printed page	136
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA (CONTINUED)	
Load Curve Chart	rollix-page-136-curve.webp SHA-256: b365d20abd4f0b07b435196acbdd3b6484e50f1f8bf590b0523638492e64ed19
Outline Drawing	rollix-page-136-drawing.webp SHA-256: e0a6758f170282a7159494349ecd2698adead9e3fcaf14967c3b4c26ec0c55b1

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-136-curve.webp | SHA-256: b365d20abd4f0b07b435196acbdd3b6484e50f1f8bf590b0523638492e64ed19

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID 26QNDMHP7VJYH2AVZSGOXZ3K53	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 136 Printed page 136
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/rollix/74-1095-01/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.