

Factory-Verified Replacement

MERYDOM 062.50.2000.001.49.1504


Certified for interchange with Rothe Erde 062.50.2000.001.49.1504. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
062.50.2000.001.49.1504	Rothe Erde 062.50.2000.001.49.1504
SERIES	STRUCTURE
06 Series	Sfere a quattro punti di contatto a una corona
OVERALL OD	OVERALL ID
2,171 mm	1,764 mm
OVERALL HEIGHT	GEAR
109 mm	Dentatura interna

Published Technical Drawing



page-084-outline.png

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	062.50.2000.001.49.1504
Certified interchangeable with	Rothe Erde 062.50.2000.001.49.1504
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	E6CKV3YZVPYPMRMBWRZFDW7UF
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Rothe Erde
Reference series	06 Series
Reference model	062.50.2000.001.49.1504
Bearing structure	Sfere a quattro punti di contatto a una corona
Gear arrangement	Dentatura interna
DIMENSION	
Raceway diameter (DL)	2.000 mm
Overall outside diameter (Da)	2.171 mm
Overall inside diameter (Di)	1.764 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	109 mm
Catalog diameter O (O)	1.998 mm
Catalog diameter U (U)	2.002 mm
Ring height H1 (H1)	100 mm
Ring height H2 (H2)	99 mm
Lower ring offset Hu (Hu)	10 mm
Upper ring offset Ho (Ho)	9 mm
Assembly weight (Weight)	843 kg
MOUNTING	
Outer ring bolt circle (La)	2.105 mm
Inner ring bolt circle (Li)	1.895 mm
Common mounting-hole count (n)	40
Common mounting-hole diameter (B)	33 mm
Metric bolt nominal size (M)	30 mm
GEAR	
Gear pitch diameter (d)	1.778 mm
Gear module (m)	14 mm
Gear tooth count (z)	127
Profile shift product x m (x*m)	-7 mm
Minimum gear face width (bmin)	99 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE	
Permitted circumferential force, normal (X1)	127,22 kN
Permitted circumferential force, maximum (X2)	254,43 kN
MISCELLANEOUS	
Grease nipple count (n1)	8
PERFORMANCE RATINGS	
Catalog Reference X1	127,22 kN Not simultaneous with other listed dynamic ratings
Catalog Reference X2	254,43 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	40 holes - B 33
Inner ring mounting	40 holes - M 30
GEAR INTERFACE	
Pitch system	module
Module reference	14 mm
Number of teeth	127
SOURCE TRACEABILITY	
Source document code	ROTHE_ERDE_CATALOG_2023
Source file	Rothe Erde.pdf
PDF page	84
Printed page	162-163
Source language	EN
Original unit system	Metric


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	page-084-load-curves.png SHA-256: 0fe510a9f16eb97d275bb0e0ec384fe8c32c2433be2fba815579f81bd5197b25
Outline Drawing	page-084-outline.png SHA-256: 0d0da1b62018e319b40e59fdf9e2dda66ac9e3733eaa7f1ccd8121e14db69631

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



page-084-load-curves.png | SHA-256: 0fe510a9f16eb97d275bb0e0ec384fe8c32c2433be2fba815579f81bd5197b25

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID**E6CKV3YZVPYYPMRMBWRZFDW7UF****SOURCE DOCUMENT****ROTHE_ERDE_CATALOG_2023****SOURCE FILE****Rothe Erde.pdf****SOURCE LOCATION****PDF page 84 | Printed page 162-163****VERIFICATION****Level 3 - MERYDOM Engineering
Verified****REVIEWED BY****MERYDOM Engineering Department**

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:

<https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/rothe-erde/062-50-2000-001-49-1504/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.