

Factory-Verified Replacement

MERYDOM RKS.160.16.1314

Certified for interchange with SKF RKS.160.16.1314. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKS.160.16.1314

REFERENCE

SKF RKS.160.16.1314

SERIES

SKF_ROLLER_MEDIUM_UNGEARED Series

STRUCTURE

Crossed Cylindrical Roller

OVERALL OD

1,399 mm

OVERALL ID

1,229 mm


OVERALL HEIGHT

mm

GEAR

Senza dentatura

Published Technical Drawing



skf-p102-outline-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKS.160.16.1314
Certified interchangeable with	SKF RKS.160.16.1314
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	V3MWVUYPO7J7N5IHXDY3X34TSS
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	SKF
Reference series	SKF_ROLLER_MEDIUM_UNGEARED Series
Reference model	RKS.160.16.1314
Bearing structure	Crossed Cylindrical Roller
Gear arrangement	Senza dentatura
DIMENSION	
Raceway diameter (dm)	1.314 mm
Overall outside diameter (D)	1.399 mm
SKF catalogue dimension D1 (D1)	1.316,5 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (d)	1.229 mm
SKF catalogue dimension d1 (d1)	1.312 mm
Mass (Mass)	135 kg
MOUNTING	
Outer ring bolt circle (Je)	1 mm
Outer ring mounting-hole specification (Ke)	36.716 mm
Outer ring mounting-hole count (Ne)	50 count
Inner ring bolt circle (Ji)	1.261 mm
Inner ring mounting-hole specification (Ki)	16 mm
Inner ring mounting-hole count (Ni)	50 count
PERFORMANCE	
Basic dynamic axial load rating (C)	421 kN
Basic static axial load rating (C0)	2.070 kN
PERFORMANCE RATINGS	
Basic Dynamic Axial	421 kN
Basic Static Axial	2.070 kN
MOUNTING INTERFACES	
Outer ring mounting	50 holes - 36716
Inner ring mounting	50 holes - 16
GEAR INTERFACE	

Complete Product Data


All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	SKF_SLEWING_BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
Source file	SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf
PDF page	102
Printed page	102
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	skf-p103-load-curve.webp SHA-256: 1288f707d28b83aaa16be687791f5a6548cc9ba2dab77a2b29da52ec8a70ce41
Outline Drawing	skf-p102-outline-drawing.webp SHA-256: 8f8ce3b41dd2fecae321ea8529676f55b7d44a7df6023e7c2412fb024a233b11

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.

Tilting moment, kNm



skf-p103-load-curve.webp | SHA-256: 1288f707d28b83aaa16be687791f5a6548cc9ba2dab77a2b29da52ec8a70ce41

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

V3MWVUYPO7J7N5IHXDY3X34TSS

SOURCE FILE

SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

SKF_SLEWING BEARINGS_PUB_BU_P2_06115_3_EN_2019_09

SOURCE LOCATION

PDF page 102 | Printed page 102

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/skf/rks-160-16-1314/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.