

Factory-Verified Replacement

MERYDOM I.616.20.00.B

Certified for interchange with Torriani Gianni I.616.20.00.B. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

**LEVEL 3 - MERYDOM ENGINEERING VERIFIED**

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

I.616.20.00.B

SERIES

I\_20\_B Series

OVERALL OD

616 mm

OVERALL HEIGHT

mm

REFERENCE

Torriani Gianni I.616.20.00.B

STRUCTURE

Sfere a quattro punti di contatto


OVERALL ID

444 mm

GEAR

Dentatura interna

Published Technical Drawing



i\_20\_b-drawing.webp

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | I.616.20.00.B                          |
| Certified interchangeable with       | Torriani Gianni I.616.20.00.B          |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | VRFWQFO7QQ4S6CUO6DBW3AYPLV             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | Torriani Gianni                        |
| Reference series                     | I_20_B Series                          |
| Reference model                      | I.616.20.00.B                          |
| Bearing structure                    | Sfere a quattro punti di contatto      |
| Gear arrangement                     | Dentatura interna                      |
| DIMENSION                            |                                        |
| Overall outside diameter (Da)        | 616 mm                                 |
| Torriani catalogue dimension U (U)   | 545,5 mm                               |
| Torriani catalogue dimension C (C)   | 542,5 mm                               |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)               |                                                              |
|-------------------------------------|--------------------------------------------------------------|
| Overall inside diameter (Di)        | 444 mm                                                       |
| Mass (Kg)                           | 42 kg                                                        |
| MOUNTING                            |                                                              |
| Outer ring bolt circle (La)         | 590 mm                                                       |
| Outer ring mounting-hole count (na) | 32                                                           |
| Inner ring bolt circle (Li)         | 505 mm                                                       |
| Inner ring mounting-hole count (ni) | 32                                                           |
| GEAR                                |                                                              |
| Gear pitch diameter (P)             | 456 mm                                                       |
| Gear module (m)                     | 6 mm                                                         |
| Gear tooth count (z)                | 76                                                           |
| PERFORMANCE                         |                                                              |
| Normal tooth force (Fz_normal)      | 13,7 kN                                                      |
| Maximum tooth force (Fz_max)        | 27,4 kN                                                      |
| PERFORMANCE RATINGS                 |                                                              |
| Rating Tooth Force Normal           | 13,7 kN   Not simultaneous with other listed dynamic ratings |
| Rating Tooth Force Max              | 27,4 kN   Not simultaneous with other listed dynamic ratings |
| MOUNTING INTERFACES                 |                                                              |
| Outer ring mounting                 | 32 holes -                                                   |
| Inner ring mounting                 | 32 holes -                                                   |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| GEAR INTERFACE            |                                                                                                             |
|---------------------------|-------------------------------------------------------------------------------------------------------------|
| Pitch system              | module                                                                                                      |
| Module reference          | 6 mm                                                                                                        |
| Number of teeth           | 76                                                                                                          |
| SOURCE TRACEABILITY       |                                                                                                             |
| Source document code      | TORRIANI_GIANNI_BALL_BEARINGS_CATALOG                                                                       |
| Source file               | catalogo-torriani-cuscinetti-a-sfere.pdf                                                                    |
| PDF page                  | 9                                                                                                           |
| Printed page              | 9                                                                                                           |
| Source language           | IT-EN                                                                                                       |
| Original unit system      | Metric                                                                                                      |
| PUBLISHED TECHNICAL MEDIA |                                                                                                             |
| Load Curve Chart          | i_20_b-static-load-curve.webp   SHA-256:<br>05ed32ed204b170ab45cf359f982502deea47462240407f0bd38d494b1f3088 |
| Outline Drawing           | i_20_b-drawing.webp   SHA-256:<br>7b3a6f6e2b004b57bf2a2eb4ea5227f55973b66d9c7bb4b8361aba7fdc<br>b61f1b      |

# Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



i\_20\_b-static-load-curve.webp | SHA-256: 05ed32ed204b170ab45cf359f982502deaaa47462240407f0bd38d494b1f3088

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

## Source and Verification Traceability

### PUBLIC RECORD UID

**VRFWQFO7QQ4S6CUO6DBW3AYPLV**

### SOURCE FILE

**catalogo-torriani-cuscinetti-a-sfere  
.pdf**

### VERIFICATION

**Level 3 - MERYDOM Engineering  
Verified**

### SOURCE DOCUMENT

**TORRIANI\_GIANNI\_BALL\_BEARINGS\_CATALOG**

### SOURCE LOCATION

**PDF page 9 | Printed page 9**

### REVIEWED BY

**MERYDOM Engineering Department**

## Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

### Request Price, Delivery and Final Engineering Confirmation

Email: [jovi@merydom.com](mailto:jovi@merydom.com) | Email: [andi@merydom.com](mailto:andi@merydom.com) | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/torriani-gianni/i-616-20-00-b/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.