

**MERYDOM SD.1200.20.00.C**

Certified for interchange with Torriani Gianni  
SD.1200.20.00.C. This document consolidates the public  
product record, complete published specifications,  
technical media, source traceability and engineering  
confirmation notes.

**LEVEL 3 - MERYDOM ENGINEERING VERIFIED**

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL  
**SD.1200.20.00.C**

REFERENCE

**Torriani Gianni SD.1200.20.00.C**

**SERIES**  
**SD\_20\_C Series**

## STRUCTURE

### Sfere a quattro punti di contatto

OVERALL OD  
**1,198 mm**


OVERALL ID  
**984 mm**

OVERALL HEIGHT  
mm

GEAR

**Senza dentatura**

## Published Technical Drawing



sd\_20\_c-drawing.webp

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | SD.1200.20.00.C                        |
| Certified interchangeable with       | Torriani Gianni SD.1200.20.00.C        |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | URVTTSKN2UIWOGJJZ2CZNSBLO2             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | Torriani Gianni                        |
| Reference series                     | SD_20_C Series                         |
| Reference model                      | SD.1200.20.00.C                        |
| Bearing structure                    | Sfere a quattro punti di contatto      |
| Gear arrangement                     | Senza dentatura                        |
| DIMENSION                            |                                        |
| Overall outside diameter (Da)        | 1.198 mm                               |
| Torriani catalogue dimension B (B)   | 1.133 mm                               |
| Torriani catalogue dimension U (U)   | 1.095,5 mm                             |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)               |                                          |
|-------------------------------------|------------------------------------------|
| Torriani catalogue dimension C (C)  | 1.092,5 mm                               |
| Torriani catalogue dimension D (D)  | 1.055 mm                                 |
| Overall inside diameter (Di)        | 984 mm                                   |
| Mass (Kg)                           | 62 kg                                    |
| MOUNTING                            |                                          |
| Outer ring bolt circle (La)         | 1.170 mm                                 |
| Outer ring mounting-hole count (na) | 16                                       |
| Inner ring bolt circle (Li)         | 1.012 mm                                 |
| Inner ring mounting-hole count (ni) | 20                                       |
| MOUNTING INTERFACES                 |                                          |
| Outer ring mounting                 | 16 holes -                               |
| Inner ring mounting                 | 20 holes -                               |
| GEAR INTERFACE                      |                                          |
| Integral gear                       | Not applicable - ungeared bearing        |
| SOURCE TRACEABILITY                 |                                          |
| Source document code                | TORRIANI_GIANNI_BALL_BEARINGS_CATALOG    |
| Source file                         | catalogo-torriani-cuscinetti-a-sfere.pdf |
| PDF page                            | 31                                       |
| Printed page                        | 31                                       |
| Source language                     | IT-EN                                    |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                               |
|---------------------------------|---------------------------------------------------------------------------------------------------------------|
| Original unit system            | Metric                                                                                                        |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                               |
| Load Curve Chart                | sd_20_c-static-load-curve.webp   SHA-256:<br>698ff28e0df4cae477de6561f03d588b2d4d7c22f93fd288bc58aa6f3bad49df |
| Outline Drawing                 | sd_20_c-drawing.webp   SHA-256:<br>10e19c5b8be13343b5d848eeb5b73b8d1fe0a4895983abb000a9801a36021c33           |

# Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



sd\_20\_c-static-load-curve.webp | SHA-256: 698ff28e0df4cae477de6561f03d588b2d4d7c22f93fd288bc58aa6f3bad49df

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

## Source and Verification Traceability

### PUBLIC RECORD UID

URVTTSKN2UIWOGJJZ2CZNSBLO2

### SOURCE FILE

catalogo-torriani-cuscinetti-a-sfere  
.pdf

### VERIFICATION

Level 3 - MERYDOM Engineering  
Verified

### SOURCE DOCUMENT

TORRIANI\_GIANNI\_BALL\_BEARINGS\_CATALOG

### SOURCE LOCATION

PDF page 31 | Printed page 31

### REVIEWED BY

MERYDOM Engineering Department

## Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

### Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:  
<https://rotnex.com/it/prodotti/cuscinetti-di-rotazione-sostitutivi/torriani-gianni/sd-1200-20-00-c/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.