

Factory-Verified Replacement

MERYDOM 32-32 2500/2-07370

Certified for interchange with IMO 32-32 2500/2-07370.
This document consolidates the public product record,
complete published specifications, technical media,
source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle,
mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

32-32 2500/2-07370

REFERENCE

IMO 32-32 2500/2-07370

SERIES

332 Series

STRUCTURE

Three-row roller

OVERALL OD

2,718 mm

OVERALL ID

2,178 mm

OVERALL HEIGHT

mm

GEAR

Internal gear

Published Technical Drawing



imo-32322500207370-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	32-32 2500/2-07370
Certified interchangeable with	IMO 32-32 2500/2-07370
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	6WGKHECG7APEXGIS3EO324MPFE
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	IMO
Reference series	332 Series
Reference model	32-32 2500/2-07370
Bearing structure	Three-row roller
Gear arrangement	Internal gear
DIMENSION	
Overall outside diameter (Da)	2,718 mm
Overall inside diameter (di)	2,178 mm
Assembly weight (G)	2,210 kg

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MOUNTING	
Outer ring bolt circle (La)	2,640 mm
Inner ring bolt circle (Li)	2,345 mm
Outer ring mounting-hole count (na)	44
GEAR	
Gear pitch diameter (d)	2,196 mm
Gear module (m)	18 mm
Gear tooth count (z)	122
Addendum modification coefficient (x)	-0.5
PERFORMANCE	
Permitted circumferential force, normal (fz_norm)	240 kN
Permitted circumferential force, maximum (fz_max)	445 kN
Static radial load rating (Co_rad)	2,189 kN
Static axial load rating, tension (Co_ax_T)	21,598 kN
Static axial load rating, compression (Co_ax_H)	13,006 kN
Dynamic radial load rating (C_rad)	1,076 kN
Dynamic axial load rating, tension (C_ax_T)	3,837 kN
Dynamic axial load rating, compression (C_ax_H)	2,720 kN
PERFORMANCE RATINGS	
Fz Norm	240 kN Not simultaneous with other listed dynamic ratings
Fz Max	445 kN Not simultaneous with other listed dynamic ratings

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
Co Rad	2,189 kN Not simultaneous with other listed dynamic ratings
Co Ax T	21,598 kN Not simultaneous with other listed dynamic ratings
Co Ax H	13,006 kN Not simultaneous with other listed dynamic ratings
C Rad	1,076 kN Not simultaneous with other listed dynamic ratings
C Ax T	3,837 kN Not simultaneous with other listed dynamic ratings
C Ax H	2,720 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	44 holes - See source drawing
Inner ring mounting	holes - See source drawing
GEAR INTERFACE	
Pitch system	module
Module reference	18 mm
Number of teeth	122
SOURCE TRACEABILITY	
Source document code	IMO_TRIPLE_ROW_ROLLER_EN
Source file	imo_rollendrehverbindung-en.pdf
PDF page	7
Printed page	Not published
Source language	EN
Original unit system	Metric


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	imo-32322500207370-curve.webp SHA-256: d3524f150c542d636e2ea2d2c3710f6b7b2055e8df3d27b9b9b901ba19ca7796
Outline Drawing	imo-32322500207370-drawing.webp SHA-256: 7eb44cf5114241ded02727fbd84edd7214e6ad2cd632020596518b2a54e57ff7

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Bearing ring material: 42CrMo4V
7 to 9 Taper type grease nipples on each circumferential row
Mounting holes equally spaced
Raceway system supplied pre-lubricated
Dimensions without tolerances DIN ISO 2768 coarse

Clearances

Position	Radial clearance	Axial clearance
1	max. 0.33	max. 0.10
2	max. 0.33	max. 0.10
3	max. 0.40	max. 0.13
4	max. 0.50	max. 0.15
5	max. 0.50	max. 0.15
6	max. 0.50	max. 0.17

imo-32322500207370-curve.webp | SHA-256: d3524f150c542d636e2ea2d2c3710f6b7b2055e8df3d27b9b9b901ba19ca7796

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID 6WGKHECG7APEXGIS3EO324MPFE	SOURCE DOCUMENT IMO_TRIPLE_ROW_ROLLER_EN
SOURCE FILE imo_rollendrehverbindung-en.pdf	SOURCE LOCATION PDF page 7 Printed page Not published
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/imo/32-32-2500-2-07370/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.