

Factory-Verified Replacement

MERYDOM VSA 200844 N

Certified for interchange with INA VSA 200844 N. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VSA 200844 N

SERIES

VSA 20 Series

OVERALL OD

950.1 mm

OVERALL HEIGHT

mm

REFERENCE

INA VSA 200844 N

STRUCTURE

Four-point contact ball


OVERALL ID

772 mm

GEAR

External gear

Published Technical Drawing



ina-g04-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VSA 200844 N
Certified interchangeable with	INA VSA 200844 N
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	MMVJM4TUCK6NEPU3QGPRP5AG6L
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	INA
Reference series	VSA 20 Series
Reference model	VSA 200844 N
Bearing structure	Four-point contact ball
Gear arrangement	External gear
DIMENSION	
Mass (Mass)	71 kg
Overall outside diameter (Da)	950.1 mm
Overall inside diameter (di)	772+0,6 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Inside centring diameter (diZT)	774 mm
Catalog diameter Di (Di)	845,5+0,6 mm
Catalog centring diameter DiZT (DiZT)	847 mm
Catalog diameter da (da)	842,5-0,6 mm
MOUNTING	
Outer ring bolt circle (La)	885 mm
Outer ring mounting-hole count (na)	36
Inner ring bolt circle (Li)	798 mm
Inner ring mounting-hole count (ni)	40
GEAR	
Gear pitch diameter (d0)	936 mm
Gear module (m)	8 mm
Gear tooth count (z)	117
PERFORMANCE	
Maximum permissible radial load (Fr perm)	148.7 kN
Normal tooth force (Fznorm)	28.3 kN
Maximum tooth force (Fzmax)	42 kN
Basic dynamic axial load rating (Ca)	222 kN
Basic static axial load rating (C0a)	1,150 kN
Basic dynamic radial load rating (Cr)	145 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Basic static radial load rating (C _{0r})	510 kN
PERFORMANCE RATINGS	
Rating Radial Static	510 kN Not simultaneous with other listed dynamic ratings
Rating Axial Static	1,150 kN Not simultaneous with other listed dynamic ratings
Rating Radial Dynamic	145 kN Not simultaneous with other listed dynamic ratings
Rating Axial Dynamic	222 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	42 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Normal	28.3 kN Not simultaneous with other listed dynamic ratings
Rating Radial Load Max	148.7 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	36 holes - See source drawing
Inner ring mounting	40 holes - See source drawing
GEAR INTERFACE	
Pitch system	module
Module reference	8 mm
Number of teeth	117
SOURCE TRACEABILITY	
Source document code	INA-SLEWING-RINGS-CATALOGUE-404-2012
Source file	404_de_en_1.pdf
PDF page	60


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.


SOURCE TRACEABILITY (CONTINUED)	
Printed page	58
Source language	EN-DE
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	ina-g04-curve.webp SHA-256: bc90ef6b06bd5b88e28acf15d86874931dcf598e3a9f103ae06adc5032440b56
Outline Drawing	ina-g04-drawing.webp SHA-256: a5869bfa877f8eacaa47abdb5a51f27f3f77bd3957cc427d2ebd639d378a5a2b

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Static limiting load diagram



Static limiting load diagram

ina-g04-curve.webp | SHA-256: bc90ef6b06bd5b88e28acf15d86874931dcf598e3a9f103ae06adc5032440b56

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID MMVJM4TUCK6NEPU3QGPRP5AG6L	SOURCE DOCUMENT INA-SLEWING-RINGS-CATALOGUE-404-2012
SOURCE FILE 404_de_en_1.pdf	SOURCE LOCATION PDF page 60 Printed page 58
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/ina/vsa-200844-n/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.