

Factory-Verified Replacement

MERYDOM VSU 250855


Certified for interchange with INA VSU 250855. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
VSU 250855	INA VSU 250855
SERIES	STRUCTURE
VSU 25 Series	Four-point contact ball
OVERALL OD	OVERALL ID
955 mm	755 mm
OVERALL HEIGHT	GEAR
mm	Ungeared

Published Technical Drawing



ina-g09-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VSU 250855
Certified interchangeable with	INA VSU 250855
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	WAF276OTSVY42A5V3HIEHSI4D
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	INA
Reference series	VSU 25 Series
Reference model	VSU 250855
Bearing structure	Four-point contact ball
Gear arrangement	Ungeared
DIMENSION	
Mass (Mass)	101 kg
Overall outside diameter (Da)	955 mm
Outside centring diameter (DaZT)	953 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Catalog diameter Di (Di)	853 mm
Catalog diameter da (da)	857 mm
Overall inside diameter (di)	755 mm
Inside centring diameter (diZT)	757 mm
MOUNTING	
Outer ring bolt circle (La)	915 mm
Inner ring bolt circle (Li)	795 mm
Common mounting-hole count (nB)	28
PERFORMANCE	
Maximum permissible radial load (Fr perm)	338.8 kN
Basic dynamic axial load rating (Ca)	485 kN
Basic static axial load rating (C0a)	2,550 kN
Basic dynamic radial load rating (Cr)	315 kN
Basic static radial load rating (C0r)	1,150 kN
Radial clearance (Radial clearance)	0,03 incl. 0,13 mm
Axial tilting clearance (Axial tilting clearance)	0,05 incl. 0,24 mm
PERFORMANCE RATINGS	
Rating Radial Static	1,150 kN Not simultaneous with other listed dynamic ratings
Rating Axial Static	2,550 kN Not simultaneous with other listed dynamic ratings
Rating Radial Dynamic	315 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.


PERFORMANCE RATINGS (CONTINUED)	
Rating Axial Dynamic	485 kN Not simultaneous with other listed dynamic ratings
Rating Radial Load Max	338.8 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	28 holes - See source drawing
Inner ring mounting	28 holes - See source drawing
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	INA-SLEWING-RINGS-CATALOGUE-404-2012
Source file	404_de_en_1.pdf
PDF page	70
Printed page	68
Source language	EN-DE
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	ina-g09-curve.webp SHA-256: 28e671cd49b81a18c7d3ea5b26ebde06b0ab2b0eb687d72a13ccd54f7b ac79c2
Outline Drawing	ina-g09-drawing.webp SHA-256: 8258cb7d7c8ac7d472e3d0fce9ce329986fc2aad585596aaf0d1bb8b88 a3e01d

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Static limiting load diagram



Static limiting load diagram

ina-g09-curve.webp | SHA-256: 28e671cd49b81a18c7d3ea5b26ebde06b0ab2b0eb687d72a13ccd54f7bac79c2

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID WAF276OTVSVY42A5V3HIEHSI4D	SOURCE DOCUMENT INA-SLEWING-RINGS-CATALOGUE-404-2012
SOURCE FILE 404_de_en_1.pdf	SOURCE LOCATION PDF page 70 Printed page 68
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/ina/vsu-250855/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.