

Factory-Verified Replacement

MERYDOM 13004001

Certified for interchange with Kaydon 13004001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

13004001

REFERENCE

Kaydon 13004001

SERIES

DT Series

STRUCTURE

Eight-point contact ball

OVERALL OD

4,318 mm

OVERALL ID

3,810 mm

OVERALL HEIGHT

250.825 mm

GEAR

Ungeared

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	13004001
Certified interchangeable with	Kaydon 13004001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	PUEK6NZ4GG43L7TKUJ4SMX4ZRV
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	DT Series
Reference model	13004001
Bearing structure	Eight-point contact ball
Gear arrangement	Ungearred
DIMENSION	
Overall outside diameter (Do)	170.000 in Metric reference: approximately 4,318 mm
Overall inside diameter (di)	150.000 in Metric reference: approximately 3,810 mm
Overall height (H)	9.875 in Metric reference: approximately 250.83 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	11950 lb Metric reference: approximately 5,420.429 kg
MOUNTING	
Outer ring bolt circle (Lo)	166.000 in Metric reference: approximately 4,216 mm
Inner ring bolt circle (Li)	154.000 in Metric reference: approximately 3,912 mm
PERFORMANCE	
Moment load rating (Crm)	8098000 ft lbf Metric reference: approximately 10,979.41 kN m
PERFORMANCE RATINGS	
Moment	8098000.0000000000 ft lbf Metric reference: approximately 10,979.41 kN m
MOUNTING INTERFACES	
Outer ring mounting	64 holes - 1.625
Inner ring mounting	64 holes - 1.625
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	88
Printed page	86
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID PUEK6NZ4GG43L7TKUJ4SMX4ZRV	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 88 Printed page 86
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/13004001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.