

Factory-Verified Replacement

MERYDOM 16268001

Certified for interchange with Kaydon 16268001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16268001

REFERENCE

Kaydon 16268001

SERIES

DT Series

STRUCTURE

Eight-point contact ball

OVERALL OD

2,265.197 mm

OVERALL ID

1,813.56 mm

OVERALL HEIGHT

180.086 mm

GEAR

External gear

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16268001
Certified interchangeable with	Kaydon 16268001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	KKDYLHDJE6UDB5INAWZQD4ZCT2
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	DT Series
Reference model	16268001
Bearing structure	Eight-point contact ball
Gear arrangement	External gear
DIMENSION	
Overall outside diameter (Do)	89.181 in Metric reference: approximately 2,265.2 mm
Overall inside diameter (di)	71.400 in Metric reference: approximately 1,814 mm
Outer ring body OD (Dr)	96.566 in Metric reference: approximately 2,452.78 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	7.090 in Metric reference: approximately 180.1 mm
Assembly weight (G)	3360 lb Metric reference: approximately 1,524.07 kg
MOUNTING	
Outer ring bolt circle (Lo)	83.622 in Metric reference: approximately 2,124 mm
Inner ring bolt circle (Li)	74.016 in Metric reference: approximately 1,880.01 mm
GEAR	
Gear pitch diameter (D2)	87.638 in Metric reference: approximately 2,226.01 mm
Gear tooth count (z2)	159
PERFORMANCE	
Maximum gear tooth load (Fz)	53760 lbf Metric reference: approximately 239.14 kN
Moment load rating (Crm)	4793200 ft lbf Metric reference: approximately 6,498.71 kN m
PERFORMANCE RATINGS	
Moment	4793200.0000000000 ft lbf Metric reference: approximately 6,498.71 kN m
Gear Tooth	53760.0000000000 lbf Metric reference: approximately 239.14 kN
MOUNTING INTERFACES	
Outer ring mounting	60 holes - 1.299
Inner ring mounting	60 holes - 1.299
GEAR INTERFACE	
Pitch system	MODULE
Module reference	14 mm
Number of teeth	159

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	92
Printed page	90
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID KKDYLHDJE6UDB5INAWZQD4ZCT2	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 92 Printed page 90
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/16268001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.