

Factory-Verified Replacement

MERYDOM 16308001

Certified for interchange with Kaydon 16308001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16308001

REFERENCE

Kaydon 16308001

SERIES

XT Series

STRUCTURE

Four-point contact ball

OVERALL OD

1,286.256 mm

OVERALL ID

958.85 mm

OVERALL HEIGHT

101.6 mm

GEAR

External gear

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16308001
Certified interchangeable with	Kaydon 16308001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	A5TNERC3ASMMI5UUXTXZLVU6I4
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	XT Series
Reference model	16308001
Bearing structure	Four-point contact ball
Gear arrangement	External gear
DIMENSION	
Overall outside diameter (Do)	50.640 in Metric reference: approximately 1,286.3 mm
Overall inside diameter (di)	37.750 in Metric reference: approximately 958.9 mm
Overall height (H)	4.000 in Metric reference: approximately 102 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	770 lb Metric reference: approximately 349.266 kg
MOUNTING	
Outer ring bolt circle (Lo)	47.000 in Metric reference: approximately 1,194 mm
Inner ring bolt circle (Li)	40.000 in Metric reference: approximately 1,016 mm
GEAR	
Gear pitch diameter (D2)	50.000 in Metric reference: approximately 1,270 mm
Diametral pitch (Pd)	2.5
Gear tooth count (z2)	125
PERFORMANCE	
Maximum gear tooth load (Fz)	27400 lbf Metric reference: approximately 121.88 kN
Moment load rating (Crm)	832000 ft lbf Metric reference: approximately 1,128.04 kN m
PERFORMANCE RATINGS	
Moment	832000.0000000000 ft lbf Metric reference: approximately 1,128.04 kN m
Gear Tooth	27400.0000000000 lbf Metric reference: approximately 121.88 kN
MOUNTING INTERFACES	
Outer ring mounting	30 holes - 1.031
Inner ring mounting	29 holes - 1.031
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	2.5 DP
Module reference	10.16 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Number of teeth	125
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	82
Printed page	80
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID A5TNERC3ASMMI5UUXTXZLVU6I4	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 82 Printed page 80
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/16308001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.