

Factory-Verified Replacement

MERYDOM 16310001

Certified for interchange with Kaydon 16310001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16310001

REFERENCE

Kaydon 16310001

SERIES

XT Series

STRUCTURE

Four-point contact ball

OVERALL OD

1,557.02 mm

OVERALL ID

1,196.975 mm

OVERALL HEIGHT

149.225 mm

GEAR

External gear

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16310001
Certified interchangeable with	Kaydon 16310001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	K4TXQEF7XCUUPDPCWTPUWONROF
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	XT Series
Reference model	16310001
Bearing structure	Four-point contact ball
Gear arrangement	External gear
DIMENSION	
Overall outside diameter (Do)	61.300 in Metric reference: approximately 1,557 mm
Overall inside diameter (di)	47.125 in Metric reference: approximately 1,196.98 mm
Outer ring body OD (Dr)	59.375 in Metric reference: approximately 1,508.13 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	5.875 in Metric reference: approximately 149.23 mm
Assembly weight (G)	1420 lb Metric reference: approximately 644.101 kg
MOUNTING	
Outer ring bolt circle (Lo)	57.375 in Metric reference: approximately 1,457.33 mm
Inner ring bolt circle (Li)	49.250 in Metric reference: approximately 1,251 mm
GEAR	
Gear pitch diameter (D2)	60.500 in Metric reference: approximately 1,537 mm
Diametral pitch (Pd)	2
Gear tooth count (z2)	121
PERFORMANCE	
Maximum gear tooth load (Fz)	40850 lbf Metric reference: approximately 181.71 kN
Moment load rating (Crm)	1522000 ft lbf Metric reference: approximately 2,063.55 kN m
PERFORMANCE RATINGS	
Moment	1522000.0000000000 ft lbf Metric reference: approximately 2,063.55 kN m
Gear Tooth	40850.0000000000 lbf Metric reference: approximately 181.71 kN
MOUNTING INTERFACES	
Outer ring mounting	40 holes - 1.063
Inner ring mounting	44 holes - 1.063
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	2 DP

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Module reference	12.7 mm
Number of teeth	121
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	82
Printed page	80
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID K4TXQEF7XCUUPDPCWTPUWONROF	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 82 Printed page 80
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/16310001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.