

Factory-Verified Replacement

MERYDOM 16345001

Certified for interchange with Kaydon 16345001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16345001

REFERENCE

Kaydon 16345001

SERIES

XR Series

STRUCTURE

Cross roller

OVERALL OD

1,790.954 mm

OVERALL ID

1,359.916 mm

OVERALL HEIGHT

128.016 mm

GEAR

External gear

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16345001
Certified interchangeable with	Kaydon 16345001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	RF3YUS22SP4DDGE23CYGBQ5ULE
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	XR Series
Reference model	16345001
Bearing structure	Cross roller
Gear arrangement	External gear
DIMENSION	
Overall outside diameter (Do)	70.510 in Metric reference: approximately 1,791 mm
Overall inside diameter (di)	53.540 in Metric reference: approximately 1,359.9 mm
Overall height (H)	5.040 in Metric reference: approximately 128 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	1460 lb Metric reference: approximately 662.245 kg
MOUNTING	
Outer ring bolt circle (Lo)	65.354 in Metric reference: approximately 1,659.99 mm
Inner ring bolt circle (Li)	55.906 in Metric reference: approximately 1,420.01 mm
GEAR	
Gear pitch diameter (D2)	68.346 in Metric reference: approximately 1,735.99 mm
Gear tooth count (z2)	124
PERFORMANCE	
Maximum gear tooth load (Fz)	36690 lbf Metric reference: approximately 163.21 kN
Moment load rating (Crm)	801340 ft lbf Metric reference: approximately 1,086.47 kN m
PERFORMANCE RATINGS	
Moment	801340.0000000000 ft lbf Metric reference: approximately 1,086.47 kN m
Gear Tooth	36690.0000000000 lbf Metric reference: approximately 163.21 kN
Dynamic Radial	293690.0000000000 lbf Metric reference: approximately 1,306.4 kN L10: 1,000,000 revolutions Not simultaneous with other listed dynamic ratings
Dynamic Thrust	332590.0000000000 lbf Metric reference: approximately 1,479.43 kN L10: 1,000,000 revolutions Not simultaneous with other listed dynamic ratings
Dynamic Moment	801340.0000000000 ft lbf Metric reference: approximately 1,086.47 kN m L10: 1,000,000 revolutions Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	42 holes - 1.063
Inner ring mounting	42 holes - 1.063

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Pitch system	MODULE
Module reference	14 mm
Number of teeth	124
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	102
Printed page	100
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID RF3YUS22SP4DDGE23CYGBQ5ULE	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 102 Printed page 100
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/16345001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.