

Factory-Verified Replacement

MERYDOM RK6-43P1Z

Certified for interchange with Kaydon RK6-43P1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RK6-43P1Z

REFERENCE

Kaydon RK6-43P1Z

SERIES

RK Series

STRUCTURE

Four-point contact ball

OVERALL OD

1,198.118 mm

OVERALL ID

984.25 mm

OVERALL HEIGHT

56.007 mm

GEAR

Ungeared

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RK6-43P1Z
Certified interchangeable with	Kaydon RK6-43P1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	SL7PMFDMP7TXF7VKCL34B3J5IE
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	RK Series
Reference model	RK6-43P1Z
Bearing structure	Four-point contact ball
Gear arrangement	Ungeared
DIMENSION	
Overall outside diameter (Do)	47.170 in Metric reference: approximately 1,198.1 mm
Overall inside diameter (di)	38.750 in Metric reference: approximately 984.3 mm
Outer ring body OD (Dr)	44.650 in Metric reference: approximately 1,134.1 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Outer ring inner diameter (Di)	43.000 in Metric reference: approximately 1,092 mm
Inner ring outer diameter (do)	42.920 in Metric reference: approximately 1,090.2 mm
Inner ring body ID (dr)	41.270 in Metric reference: approximately 1,048.3 mm
Overall height (H)	2.205 in Metric reference: approximately 56.01 mm
Assembly weight (G)	153 lb Metric reference: approximately 69.4 kg
MOUNTING	
Outer ring bolt circle (Lo)	46.000 in Metric reference: approximately 1,168 mm
Inner ring bolt circle (Li)	39.880 in Metric reference: approximately 1,013 mm
PERFORMANCE	
Moment load rating (Crm)	75500 ft lbf Metric reference: approximately 102.36 kN m
PERFORMANCE RATINGS	
Moment	75500.0000000000 ft lbf Metric reference: approximately 102.36 kN m
MOUNTING INTERFACES	
Outer ring mounting	18 holes - 0.688 through, equally spaced
Inner ring mounting	24 holes - 0.688 through, equally spaced
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	50

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Printed page	48
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID

SL7PMFDMP7TXF7VKCL34B3J5IE

SOURCE DOCUMENT

KAYDON-CAT390

SOURCE FILE

Kaydon_Catalog_390.pdf

SOURCE LOCATION

PDF page 50 | Printed page 48

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1
- Confirm the exact model designation and all installation-envelope dimensions.
- 2
- Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3
- Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4
- Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5
- Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6
- Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/kaydon/rk6-43p1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.