

Factory-Verified Replacement

MERYDOM V25E257

Certified for interchange with La Leonessa V25E257. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

V25E257

SERIES

1RE Series

OVERALL OD

723 mm

OVERALL HEIGHT

100 mm

REFERENCE

La Leonessa V25E257

STRUCTURE

Four-point contact ball


OVERALL ID

470 mm

GEAR

External gear

Published Technical Drawing



la-leonessa-1re-drawing.webp



## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | V25E257                                |
| Certified interchangeable with       | La Leonessa V25E257                    |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | WMXEAJKBMMYEE7L2HSGIOBRKJK             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | La Leonessa                            |
| Reference series                     | 1RE Series                             |
| Reference model                      | V25E257                                |
| Bearing structure                    | Four-point contact ball                |
| Gear arrangement                     | External gear                          |
| DIMENSION                            |                                        |
| Mass (P)                             | 137 kg                                 |
| Overall outside diameter (De)        | 723 mm                                 |
| Overall inside diameter (Di)         | 470 mm                                 |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                          |          |
|------------------------------------------------|----------|
| Overall height (H)                             | 100 mm   |
| Dim Dr (Dr)                                    | 574.5 mm |
| MOUNTING                                       |          |
| Outer ring bolt circle (Ie)                    | 640 mm   |
| Outer ring mounting-hole count (ne)            | 36       |
| Outer ring mounting-hole specification (Me)    | M16      |
| Inner ring bolt circle (Ii)                    | 508 mm   |
| Inner ring mounting-hole count (ni)            | 36-1     |
| Inner ring mounting-hole specification (Mi)    | M16      |
| GEAR                                           |          |
| Gear module (m)                                | 10 mm    |
| Gear tooth count (z)                           | 70       |
| Addendum modification product x*m (xm)         | 3.5 mm   |
| Liebherr catalogue gear dimension k*m (km)     | 2 mm     |
| Gear pitch diameter (Dp)                       | 707 mm   |
| Gear Tooth Height (Hd)                         | 90 mm    |
| Gear Hardening Indicator (Temp <sub>ra</sub> ) |          |
| PERFORMANCE                                    |          |
| Basic static axial load rating (C0a)           | 2,060 kN |
| Static tilting moment rating (M0r)             | 235 kNm  |

# Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| PERFORMANCE (CONTINUED)                 |                                                               |
|-----------------------------------------|---------------------------------------------------------------|
| Normal tooth force (F <sub>nom</sub> )  | 94 kN                                                         |
| Maximum tooth force (F <sub>max</sub> ) | 188 kN                                                        |
| MISCELLANEOUS                           |                                                               |
| Pattern (Schema)                        | B                                                             |
| PERFORMANCE RATINGS                     |                                                               |
| Rating Axial Static                     | 2,060 kN   Not simultaneous with other listed dynamic ratings |
| Rating Tilting Moment Static            | 235 kNm   Not simultaneous with other listed dynamic ratings  |
| Rating Tooth Force Normal               | 94 kN   Not simultaneous with other listed dynamic ratings    |
| Rating Tooth Force Max                  | 188 kN   Not simultaneous with other listed dynamic ratings   |
| MOUNTING INTERFACES                     |                                                               |
| Outer ring mounting                     | 36 holes - 36; M16                                            |
| Inner ring mounting                     | 36 holes - 36-1; M16                                          |
| GEAR INTERFACE                          |                                                               |
| Pitch system                            | module                                                        |
| Module reference                        | 10 mm                                                         |
| Number of teeth                         | 70                                                            |
| SOURCE TRACEABILITY                     |                                                               |
| Source document code                    | LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017                        |
| Source file                             | SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf                       |
| PDF page                                | 4                                                             |
| Printed page                            | 4                                                             |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                                       |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Source language                 | EN                                                                                                                    |
| Original unit system            | Metric                                                                                                                |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                                       |
| Load Curve Chart                | la-leonessa-1re-static_load_curve.webp   SHA-256:<br>d7aae043a7185155fb61d59e50819f72c59987082f018cd5cc43cc5387066075 |
| Outline Drawing                 | la-leonessa-1re-drawing.webp   SHA-256:<br>9def12f376fbd9bc222f66ab0503412bd5a475fdfe624e4dbfe0ca549ea4d61f           |

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-1re-static\_load\_curve.webp | SHA-256:  
d7aae043a7185155fb61d59e50819f72c59987082f018cd5cc43cc5387066075

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

|                                                                           |                                                                              |
|---------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <div>PUBLIC RECORD UID</div> <div>WMXEAJKBMMYEE7L2HSGIOBRKJK</div>        | <div>SOURCE DOCUMENT</div> <div>LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017</div> |
| <div>SOURCE FILE</div> <div>SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf</div> | <div>SOURCE LOCATION</div> <div>PDF page 4   Printed page 4</div>            |
| <div>VERIFICATION</div> <div>Level 3 - MERYDOM Engineering Verified</div> | <div>REVIEWED BY</div> <div>MERYDOM Engineering Department</div>             |

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/la-leonessa/v25e257/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.