

Factory-Verified Replacement

MERYDOM VE202B00

Certified for interchange with La Leonessa VE202B00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VE202B00

SERIES

2SE Series

OVERALL OD

2,025 mm

OVERALL HEIGHT

146 mm

REFERENCE

La Leonessa VE202B00

STRUCTURE

Double-row ball

OVERALL ID

1,608 mm

GEAR

External gear

Published Technical Drawing



la-leonessa-2se-drawing.webp



## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | VE202B00                               |
| Certified interchangeable with       | La Leonessa VE202B00                   |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | WQTBKQ6EYUJMNTYNWBFTX2WCHQ             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | La Leonessa                            |
| Reference series                     | 2SE Series                             |
| Reference model                      | VE202B00                               |
| Bearing structure                    | Double-row ball                        |
| Gear arrangement                     | External gear                          |
| DIMENSION                            |                                        |
| Mass (P)                             | 1,000 kg                               |
| Overall outside diameter (De)        | 2,025 mm                               |
| Overall inside diameter (Di)         | 1,608 mm                               |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                         |            |
|-----------------------------------------------|------------|
| Overall height (H)                            | 146 mm     |
| Dim Dr (Dr)                                   | 1,790.5 mm |
| MOUNTING                                      |            |
| Outer ring bolt circle (Ie)                   | 1,905 mm   |
| Outer ring mounting-hole count (ne)           | 60         |
| Outer ring mounting-hole specification (Me)   | M27        |
| Inner ring bolt circle (Ii)                   | 1,675 mm   |
| Inner ring mounting-hole count (ni)           | 60         |
| Inner ring mounting-hole specification (Mi)   | M27        |
| GEAR                                          |            |
| Gear module (m)                               | 12 mm      |
| Gear tooth count (z)                          | 166        |
| Addendum modification product $x^*m$ (xm)     | 6 mm       |
| Liebherr catalogue gear dimension $k^*m$ (km) | 1.5 mm     |
| Gear pitch diameter (Dp)                      | 2,004 mm   |
| Gear Tooth Height (Hd)                        | 120 mm     |
| PERFORMANCE                                   |            |
| Basic static axial load rating (C0a)          | 14,160 kN  |
| Static tilting moment rating (M0r)            | 5,988 kNm  |
| Normal tooth force (Fnom)                     | 168 kN     |

# Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| PERFORMANCE (CONTINUED)      |                                                                |
|------------------------------|----------------------------------------------------------------|
| Maximum tooth force (Fmax)   | 336 kN                                                         |
| MISCELLANEOUS                |                                                                |
| Pattern (Schema)             | B                                                              |
| PERFORMANCE RATINGS          |                                                                |
| Rating Axial Static          | 14,160 kN   Not simultaneous with other listed dynamic ratings |
| Rating Tilting Moment Static | 5,988 kNm   Not simultaneous with other listed dynamic ratings |
| Rating Tooth Force Normal    | 168 kN   Not simultaneous with other listed dynamic ratings    |
| Rating Tooth Force Max       | 336 kN   Not simultaneous with other listed dynamic ratings    |
| MOUNTING INTERFACES          |                                                                |
| Outer ring mounting          | 60 holes - 60; M27                                             |
| Inner ring mounting          | 60 holes - 60; M27                                             |
| GEAR INTERFACE               |                                                                |
| Pitch system                 | module                                                         |
| Module reference             | 12 mm                                                          |
| Number of teeth              | 166                                                            |
| SOURCE TRACEABILITY          |                                                                |
| Source document code         | LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017                         |
| Source file                  | SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf                        |
| PDF page                     | 12                                                             |
| Printed page                 | 12                                                             |
| Source language              | EN                                                             |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                                       |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Original unit system            | Metric                                                                                                                |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                                       |
| Load Curve Chart                | la-leonessa-2se-static_load_curve.webp   SHA-256:<br>0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1 |
| Outline Drawing                 | la-leonessa-2se-drawing.webp   SHA-256:<br>9def12f376fbd9bc222f66ab0503412bd5a475fdfe624e4dbfe0ca549ea4d61f           |

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-2se-static\_load\_curve.webp | SHA-256:  
0056d7fd4ded2922ffa0000f4b2784841e0dbba7de039b531b9334852625cba1

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

|                                                                               |                                                                              |
|-------------------------------------------------------------------------------|------------------------------------------------------------------------------|
| <div>PUBLIC RECORD UID</div> <div>WQTBKQ6EYUJMNNTYNWBFTX2WCHQ</div>           | <div>SOURCE DOCUMENT</div> <div>LA-LEONESSA-EXTERNAL-GEAR-CATALOG-2017</div> |
| <div>SOURCE FILE</div> <div>SLEWING-BEARINGS-WITH-EXTERNAL-GEAR.pdf</div>     | <div>SOURCE LOCATION</div> <div>PDF page 12   Printed page 12</div>          |
| <div>VERIFICATION</div> <div>Level 3 - MERYDOM Engineering<br/>Verified</div> | <div>REVIEWED BY</div> <div>MERYDOM Engineering Department</div>             |

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/la-leonessa/ve202b00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.