

Factory-Verified Replacement

MERYDOM VS070UE00

Certified for interchange with La Leonessa VS070UE00.
This document consolidates the public product record,
complete published specifications, technical media,
source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle,
mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VS070UE00

SERIES

U_UNGEARED Series

OVERALL OD

700 mm

OVERALL HEIGHT

82 mm

REFERENCE

La Leonessa VS070UE00

STRUCTURE

Flanged Four Point Contact Ball


OVERALL ID

530 mm

GEAR

Ungeared

Published Technical Drawing



la-leonessa-u-ungeared-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	VS070UE00
Certified interchangeable with	La Leonessa VS070UE00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	DOCL5SUT5ZDGAZ3AGRLHTBPB2E
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	La Leonessa
Reference series	U_UNGEARED Series
Reference model	VS070UE00
Bearing structure	Flanged Four Point Contact Ball
Gear arrangement	Ungeared
DIMENSION	
Mass (P)	63 kg
Overall outside diameter (De)	700 mm
Overall inside diameter (Di)	530 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	82 mm
Dim Dr (Dr)	593 mm
MOUNTING	
Outer ring bolt circle (Ie)	670 mm
Outer ring mounting-hole count (ne)	24
Outer ring mounting-hole specification (Me)	M16
Inner ring bolt circle (Ii)	670 mm
Inner ring mounting-hole count (ni)	24
Inner ring mounting-hole specification (Mi)	M16
PERFORMANCE	
Basic static axial load rating (C0a)	480 kN
Static tilting moment rating (M0r)	61 kNm
PERFORMANCE RATINGS	
Rating Axial Static	480 kN Not simultaneous with other listed dynamic ratings
Rating Tilting Moment Static	61 kNm Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	24 holes - 24; M16
Inner ring mounting	24 holes - 24; M16
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY	
Source document code	LA-LEONESSA-FLANGED-SLEWING-BEARINGS-CATALOG-2013
Source file	Catalogo_flangiati.pdf
PDF page	4
Printed page	4
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	la-leonessa-u-ungeared-static_load_curve.webp SHA-256: 0553d34f9cf6ecace85df68d0da0df4223dbed9c99adc6912336f77a690667e1
Outline Drawing	la-leonessa-u-ungeared-drawing.webp SHA-256: 42f3a5492011f1959d4332265d022bdb981762b0d33a1b760fe108e682b94ba7

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



la-leonessa-u-ungeared-static_load_curve.webp | SHA-256:
0553d34f9cf6ecace85df68d0da0df4223dbed9c99adc6912336f77a690667e1

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

DOCL5SUT5ZDGAZ3AGRLHTBPB2E

SOURCE FILE

Catalogo_flangiati.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

**LA-LEONESSA-FLANGED-SLEWING-BEARINGS
-CATALOG-2013**

SOURCE LOCATION

PDF page 4 | Printed page 4

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/la-leonessa/vs070ue00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.