

Factory-Verified Replacement

MERYDOM KUD01697-030WA15-900-000

Certified for interchange with Liebherr KUD01697-030WA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

KUD01697-030WA15-900-000

REFERENCE

Liebherr KUD01697-030WA15-900-000

SERIES

KUD_30_WA Series

STRUCTURE

Double-row four-point contact ball

OVERALL OD

1,869.6 mm

OVERALL ID

1,583 mm


OVERALL HEIGHT

123 mm

GEAR

External gear

Published Technical Drawing



liebherr-page-112-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	KUD01697-030WA15-900-000
Certified interchangeable with	Liebherr KUD01697-030WA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	VAIJHL3VXVFCC56UAN32APW56Z
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	KUD_30_WA Series
Reference model	KUD01697-030WA15-900-000
Bearing structure	Double-row four-point contact ball
Gear arrangement	External gear
DIMENSION	
Mass (Weight)	577 kg
Overall outside diameter (Da)	1,869.6 mm
Overall inside diameter (Di)	1,583 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	123 mm
Liebherr catalogue dimension O (O)	1,695 mm
Liebherr catalogue dimension U (U)	1,699 mm
Liebherr catalogue dimension H1 (H1)	111 mm
Liebherr catalogue dimension H2 (H2)	111 mm
MOUNTING	
Outer ring bolt circle (La)	1,764 mm
Inner ring bolt circle (Li)	1,627 mm
La/Li mounting-hole count (n)	52
Mounting fastener specification (M)	20
Liebherr catalogue count n1 (n1)	7
GEAR	
Gear pitch diameter (d)	1,836 mm
Gear module (m)	12 mm
Gear tooth count (z)	153
Addendum modification product x^*m (x^*m)	6 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-1.2 mm
Gear face width (b)	111 mm
PERFORMANCE	
Standard tooth force (Fz standard)	128.7 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	257.4 kN
Static load rating (Cstat)	14,842 kN
Dynamic load rating (Cdyn)	1,102 kN
PERFORMANCE RATINGS	
Rating Dynamic	1,102 kN Not simultaneous with other listed dynamic ratings
Rating Static	14,842 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	257.4 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	128.7 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	52 holes - 20
Inner ring mounting	52 holes - 20
GEAR INTERFACE	
Pitch system	module
Module reference	12 mm
Number of teeth	153
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	112
Printed page	112


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-112-curve.webp SHA-256: 894c66078bf8be12226dff072482878c470ba617a6dfb533e8a204e474512c7
Outline Drawing	liebherr-page-112-drawing.webp SHA-256: c923787016501ada475c415e443d8ba58133ea972b468b4aca029949fe2299c9

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-112-curve.webp | SHA-256: 894c66078bf8be12226dfffb072482878c470ba617a6dfb533e8a204e474512c7

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID VAIJHL3VXVFCC56UAN32APW56Z	SOURCE DOCUMENT LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
SOURCE FILE liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf	SOURCE LOCATION PDF page 112 Printed page 112
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/liebherr/kud01697-030wa15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.