


MERYDOM 06-1116-00

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

External gear



rollix-page-102-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	06-1116-00
Certified interchangeable with	ROLLIX 06-1116-00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	JYRWU2JJ2LXC6245DQV4KSBDVQ
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	06 Series
Reference model	06-1116-00
Bearing structure	Single-row crossed roller
Gear arrangement	External gear
DIMENSION	
Overall height (HT)	114 mm
Overall outside diameter (Dia De)	1,289.5 mm
Outer ring height (He)	90 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	984 mm
Inner ring height (Hi)	94 mm
Assembly weight (Weight)	327 kg
MOUNTING	
Outer ring pilot diameter (Dia Ce)	1,240 mm
Inner ring pilot diameter (Dia Ci)	985 mm
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	1,198 mm
Outer ring mounting-hole count (Ne)	40
Outer ring mounting-hole specification (Dhe)	22 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	1,035 mm
Inner ring mounting-hole count (Ni)	40
Inner ring mounting-hole specification (Dhi)	22 mm
GEAR	
Gear module (Module)	10 mm
Gear tooth count (Z)	125
Gear face width (W)	78 mm
PERFORMANCE	
Gear capacity, unhardened (Gear capacity unhardened)	116 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Gear capacity, hardened (Gear capacity hardened)	155 kN
MISCELLANEOUS	
Ring with greasing holes (Ring with greasing holes)	E+I
Greasing hole type (Greasing hole type)	F+R
PERFORMANCE RATINGS	
Rating Gear Capacity Hardened	155 kN Not simultaneous with other listed dynamic ratings
Rating Gear Capacity Unhardened	116 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	40 holes - External ring hole type Th; Dhe 22 mm
Inner ring mounting	40 holes - Inner ring hole type Th; Dhi 22 mm
GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	125
SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	102
Printed page	102
Source language	EN


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-102-curve.webp SHA-256: 0339bb5e08087bf13ed46e3693a4304c9c7736fb83e8c6269e0a1b687c60d70b
Outline Drawing	rollix-page-102-drawing.webp SHA-256: a5736d9cad0fde539f2570119068ca06caaaedd1bc75c37763ca7927829b61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-102-curve.webp | SHA-256: 0339bb5e08087bf13ed46e3693a4304c9c7736fb83e8c6269e0a1b687c60d70b

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID JYRWU2JJ2LXC6245DQV4KSBDVQ	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 102 Printed page 102
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rollix/06-1116-00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.