


MERYDOM 06-5000-00

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

External gear



rollix-page-103-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	06-5000-00
Certified interchangeable with	ROLLIX 06-5000-00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	K7H74CN4TTABZSGQQNYXCTSGRI
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	06 Series
Reference model	06-5000-00
Bearing structure	Single-row crossed roller
Gear arrangement	External gear
DIMENSION	
Overall height (HT)	215 mm
Overall outside diameter (Dia De)	5,364 mm
Outer ring height (He)	200 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	4,724 mm
Inner ring height (Hi)	185 mm
Assembly weight (Weight)	6,383 kg
MOUNTING	
Outer ring pilot diameter (Dia Ce)	5,012 mm
Inner ring pilot diameter (Dia Ci)	4,728 mm
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	5,166 mm
Outer ring mounting-hole count (Ne)	126
Outer ring mounting-hole specification (Dhe)	45 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	4,834 mm
Inner ring mounting-hole count (Ni)	126
Inner ring mounting-hole specification (Dhi)	45 mm
GEAR	
Gear module (Module)	22 mm
Gear tooth count (Z)	241
Gear face width (W)	200 mm
PERFORMANCE	
Gear capacity, unhardened (Gear capacity unhardened)	882 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Gear capacity, hardened (Gear capacity hardened)	1,026 kN
MISCELLANEOUS	
Ring with greasing holes (Ring with greasing holes)	I
Greasing hole type (Greasing hole type)	R
PERFORMANCE RATINGS	
Rating Gear Capacity Hardened	1,026 kN Not simultaneous with other listed dynamic ratings
Rating Gear Capacity Unhardened	882 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	126 holes - External ring hole type Th; Dhe 45 mm
Inner ring mounting	126 holes - Inner ring hole type Th; Dhi 45 mm
GEAR INTERFACE	
Pitch system	module
Module reference	22 mm
Number of teeth	241
SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	103
Printed page	103
Source language	EN


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-103-curve.webp SHA-256: 11762ccf3814c0d7b985627797dc2ae88086c07b96639b1337131d1fb55cbf1a
Outline Drawing	rollix-page-103-drawing.webp SHA-256: a5736d9cad0fde539f2570119068ca06caaaaedd1bc75c37763ca7927829b61f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-103-curve.webp | SHA-256: 11762ccf3814c0d7b985627797dc2ae88086c07b96639b1337131d1fb55cbf1a

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID K7H74CN4TTABZSGQQNYXCTSGRI	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 103 Printed page 103
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rollix/06-5000-00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.