

Factory-Verified Replacement

MERYDOM 26-0411-01

Certified for interchange with ROLLIX 26-0411-01. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

26-0411-01

REFERENCE

ROLLIX 26-0411-01

SERIES

26 Series

STRUCTURE

Light-series ball bearing

OVERALL OD

518 mm

OVERALL ID

304 mm


OVERALL HEIGHT

56 mm

GEAR

Ungeared

Published Technical Drawing



rollix-page-093-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	26-0411-01
Certified interchangeable with	ROLLIX 26-0411-01
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	K23JFLCFSJIIFJZGTP5K4B3AST
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	26 Series
Reference model	26-0411-01
Bearing structure	Light-series ball bearing
Gear arrangement	Ungeared
DIMENSION	
Overall height (HT)	56 mm
Overall outside diameter (Dia De)	518 mm
Outer ring height (He)	46 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	304 mm
Inner ring height (Hi)	46 mm
Assembly weight (Weight)	25 kg
MOUNTING	
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	490 mm
Outer ring mounting-hole count (Ne)	8
Outer ring mounting-hole specification (Dhe)	18 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	332 mm
Inner ring mounting-hole count (Ni)	12
Inner ring mounting-hole specification (Dhi)	18 mm
MISCELLANEOUS	
Ring with greasing holes (Ring with greasing holes)	E+I
Greasing hole type (Greasing hole type)	R
MOUNTING INTERFACES	
Outer ring mounting	8 holes - External ring hole type Th; Dhe 18 mm
Inner ring mounting	12 holes - Inner ring hole type Th; Dhi 18 mm
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	93
Printed page	93
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-093-curve.webp SHA-256: 713fcb3c1856f1b74646f077a9f245fc319be4ea1dd085d54dc2cc7e2d6fd779
Outline Drawing	rollix-page-093-drawing.webp SHA-256: ab2db7743fc8f7036a400c9730945285a043c4536041ce5fd5e1e2ffd3d8c397

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-093-curve.webp | SHA-256: 713fcb3c1856f1b74646f077a9f245fc319be4ea1dd085d54dc2cc7e2d6fd779

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID K23JFLCFSJIIFJZGTP5K4B3AST	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 93 Printed page 93
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rollix/26-0411-01/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.