

Factory-Verified Replacement

MERYDOM 092.40.2003.991.41.1502

Certified for interchange with Rothe Erde 092.40.2003.991.41.1502. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

092.40.2003.991.41.1502

SERIES

09 Series

OVERALL OD

2,192 mm

OVERALL HEIGHT

148 mm

REFERENCE

Rothe Erde 092.40.2003.991.41.1502

STRUCTURE

Double-row four-point contact ball


OVERALL ID

1,750 mm

GEAR

Internal gear

Published Technical Drawing



page-092-outline.png

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | 092.40.2003.991.41.1502                |
| Certified interchangeable with       | Rothe Erde 092.40.2003.991.41.1502     |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | CCIZZ6QZBYI5LKYLJSQB6JTHJO             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | Rothe Erde                             |
| Reference series                     | 09 Series                              |
| Reference model                      | 092.40.2003.991.41.1502                |
| Bearing structure                    | Double-row four-point contact ball     |
| Gear arrangement                     | Internal gear                          |
| DIMENSION                            |                                        |
| Raceway diameter (DL)                | 2,003 mm                               |
| Overall outside diameter (Da)        | 2,192 mm                               |
| Overall inside diameter (Di)         | 1,750 mm                               |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                     |          |
|-------------------------------------------|----------|
| Overall height (H)                        | 148 mm   |
| Catalog diameter O (O)                    | 2,001 mm |
| Catalog diameter U (U)                    | 2,011 mm |
| Ring height H1 (H1)                       | 139 mm   |
| Ring height H2 (H2)                       | 139 mm   |
| Lower ring offset Hu (Hu)                 | 9 mm     |
| Upper ring offset Ho (Ho)                 | 9 mm     |
| Assembly weight (Weight)                  | 1,221 kg |
| MOUNTING                                  |          |
| Outer ring bolt circle (La)               | 2,113 mm |
| Inner ring bolt circle (Li)               | 1,899 mm |
| Common mounting-hole count (n)            | 60       |
| Common mounting-hole diameter (B)         | 36 mm    |
| Metric bolt nominal size (M)              | 33 mm    |
| GEAR                                      |          |
| Gear pitch diameter (d)                   | 1,764 mm |
| Gear module (m)                           | 14 mm    |
| Gear tooth count (z)                      | 126      |
| Profile shift product x m (x*m)           | -7 mm    |
| Tip-height modification product k m (k*m) | 0 mm     |

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| GEAR (CONTINUED)                              |                                                             |
|-----------------------------------------------|-------------------------------------------------------------|
| Minimum gear face width (bmin)                | 138 mm                                                      |
| Root-neck diameter Zu (Zu)                    | 1,819 mm                                                    |
| PERFORMANCE                                   |                                                             |
| Permitted circumferential force, normal (X1)  | 168 kN                                                      |
| Permitted circumferential force, maximum (X2) | 336 kN                                                      |
| MISCELLANEOUS                                 |                                                             |
| Grease nipple count (n1)                      | 10                                                          |
| PERFORMANCE RATINGS                           |                                                             |
| Catalog Reference X1                          | 168 kN   Not simultaneous with other listed dynamic ratings |
| Catalog Reference X2                          | 336 kN   Not simultaneous with other listed dynamic ratings |
| MOUNTING INTERFACES                           |                                                             |
| Outer ring mounting                           | 60 holes - B 36                                             |
| Inner ring mounting                           | 60 holes - M 33                                             |
| GEAR INTERFACE                                |                                                             |
| Pitch system                                  | module                                                      |
| Module reference                              | 14 mm                                                       |
| Number of teeth                               | 126                                                         |
| SOURCE TRACEABILITY                           |                                                             |
| Source document code                          | ROTHE_ERDE_CATALOG_2023                                     |
| Source file                                   | Rothe Erde.pdf                                              |
| PDF page                                      | 92                                                          |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| SOURCE TRACEABILITY (CONTINUED) |                                                                                                         |
|---------------------------------|---------------------------------------------------------------------------------------------------------|
| Printed page                    | 178-179                                                                                                 |
| Source language                 | EN                                                                                                      |
| Original unit system            | Metric                                                                                                  |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                         |
| Load Curve Chart                | page-092-load-curves.png   SHA-256:<br>4542dbf981be5d22df4700b44bf3c89b045395e558a7fc39dfc4ebcec7745d9b |
| Outline Drawing                 | page-092-outline.png   SHA-256:<br>c025164dd9c380f3e04a3029b604345eb22e768de39b68c1bc72dbb242b3fc95     |

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



page-092-load-curves.png | SHA-256: 4542dbf981be5d22df4700b44bf3c89b045395e558a7fc39dfc4ebcec7745d9b

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

|                                                                               |                                                                          |
|-------------------------------------------------------------------------------|--------------------------------------------------------------------------|
| <div>PUBLIC RECORD UID</div> <div>CCIZZ6QZBYI5LKYLJSQB6JTHJO</div>            | <div>SOURCE DOCUMENT</div> <div>ROTHE_ERDE_CATALOG_2023</div>            |
| <div>SOURCE FILE</div> <div>Rothe Erde.pdf</div>                              | <div>SOURCE LOCATION</div> <div>PDF page 92   Printed page 178-179</div> |
| <div>VERIFICATION</div> <div>Level 3 - MERYDOM Engineering<br/>Verified</div> | <div>REVIEWED BY</div> <div>MERYDOM Engineering Department</div>         |

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rothe-erde/092-40-2003-991-41-1502/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.