

MERYDOM 191.25.2240.990.41.1502

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	191.25.2240.990.41.1502
Certified interchangeable with	Rothe Erde 191.25.2240.990.41.1502
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	XVUBQGIZXK32KMMS25ZMPHCZB
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Rothe Erde
Reference series	19 Series
Reference model	191.25.2240.990.41.1502
Bearing structure	Three-row roller
Gear arrangement	External gear
DIMENSION	
Raceway diameter (DL)	2,240 mm
Overall outside diameter (Da)	2,516.4 mm
Overall inside diameter (Di)	2,059 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	147 mm
Catalog diameter O (O)	2,276 mm
Catalog diameter U (U)	2,266 mm
Ring height H1 (H1)	117 mm
Ring height H2 (H2)	138 mm
Lower ring offset Hu (Hu)	9 mm
Upper ring offset Ho (Ho)	30 mm
Assembly weight (Weight)	1,378 kg
MOUNTING	
Outer ring bolt circle (La)	2,366 mm
Inner ring bolt circle (Li)	2,125 mm
Common mounting-hole count (n)	48
Common mounting-hole diameter (B)	33 mm
Metric bolt nominal size (M)	30 mm
GEAR	
Gear pitch diameter (d)	2,466 mm
Gear module (m)	18 mm
Gear tooth count (z)	137
Profile shift product x m (x*m)	9 mm
Tip-height modification product k m (k*m)	-1.8 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR (CONTINUED)	
Minimum gear face width (bmin)	116 mm
PERFORMANCE	
Permitted circumferential force, normal (X1)	181.57 kN
Permitted circumferential force, maximum (X2)	363.13 kN
MISCELLANEOUS	
Grease nipple count (n1)	8
PERFORMANCE RATINGS	
Catalog Reference X1	181.57 kN Not simultaneous with other listed dynamic ratings
Catalog Reference X2	363.13 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - M 30
Inner ring mounting	48 holes - B 33
GEAR INTERFACE	
Pitch system	module
Module reference	18 mm
Number of teeth	137
SOURCE TRACEABILITY	
Source document code	ROTHERDE_CATALOG_2023
Source file	Rothe Erde.pdf
PDF page	97
Printed page	188-189

Complete Product Data


All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	page-097-load-curves.png SHA-256: bab207dd77a40f2adf093523d5798e0d5b43bec92649e74b651c9712cc36f566
Outline Drawing	page-097-outline.png SHA-256: 76b41f3a72e4f2995e3b8c9e006f3772ee466d177c6823093f4d1a9ac785e998


Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.

Static boundary load curves



Utilization period curves – 30 000 revolutions



page-097-load-curves.png | SHA-256: bab207dd77a40f2adf093523d5798e0d5b43bec92649e74b651c9712cc36f566

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID XVUBQGIZXK32KMMS25ZMPHZCZB	SOURCE DOCUMENT ROTHE_ERDE_CATALOG_2023
SOURCE FILE Rothe Erde.pdf	SOURCE LOCATION PDF page 97 Printed page 188-189
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rothe-erde/191-25-2240-990-41-1502/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.