

Factory-Verified Replacement

MERYDOM 191.40.2800.990.41.1502

Certified for interchange with Rothe Erde 191.40.2800.990.41.1502. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL
191.40.2800.990.41.1502

REFERENCE
Rothe Erde 191.40.2800.990.41.1502

SERIES
19 Series

STRUCTURE
Three-row roller


OVERALL OD
3,136 mm

OVERALL ID
2,562 mm

OVERALL HEIGHT
220 mm

GEAR
External gear

Published Technical Drawing



page-101-outline.png

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	191.40.2800.990.41.1502
Certified interchangeable with	Rothe Erde 191.40.2800.990.41.1502
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	T3YGDDG3I3AZ7TK3WJFEIZMJi6
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Rothe Erde
Reference series	19 Series
Reference model	191.40.2800.990.41.1502
Bearing structure	Three-row roller
Gear arrangement	External gear
DIMENSION	
Raceway diameter (DL)	2,800 mm
Overall outside diameter (Da)	3,136 mm
Overall inside diameter (Di)	2,562 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	220 mm
Catalog diameter O (O)	2,850 mm
Catalog diameter U (U)	2,837 mm
Ring height H1 (H1)	170 mm
Ring height H2 (H2)	210 mm
Lower ring offset Hu (Hu)	10 mm
Upper ring offset Ho (Ho)	50 mm
Assembly weight (Weight)	3,267 kg
MOUNTING	
Outer ring bolt circle (La)	2,965 mm
Inner ring bolt circle (Li)	2,640 mm
Common mounting-hole count (n)	48
Common mounting-hole diameter (B)	39 mm
Metric bolt nominal size (M)	36 mm
GEAR	
Gear pitch diameter (d)	3,080 mm
Gear module (m)	20 mm
Gear tooth count (z)	154
Profile shift product x m (x*m)	10 mm
Tip-height modification product k m (k*m)	-2 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR (CONTINUED)	
Minimum gear face width (bmin)	169 mm
PERFORMANCE	
Permitted circumferential force, normal (X1)	293.91 kN
Permitted circumferential force, maximum (X2)	587.83 kN
MISCELLANEOUS	
Grease nipple count (n1)	8
PERFORMANCE RATINGS	
Catalog Reference X1	293.91 kN Not simultaneous with other listed dynamic ratings
Catalog Reference X2	587.83 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - M 36
Inner ring mounting	48 holes - B 39
GEAR INTERFACE	
Pitch system	module
Module reference	20 mm
Number of teeth	154
SOURCE TRACEABILITY	
Source document code	ROTHE_ERDE_CATALOG_2023
Source file	Rothe Erde.pdf
PDF page	101
Printed page	196-197


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	page-101-load-curves.png SHA-256: 9f2a339ba61d022ee055d3b4ebd6eef03bd1653cff253d94d3607246d27991f0
Outline Drawing	page-101-outline.png SHA-256: 76b41f3a72e4f2995e3b8c9e006f3772ee466d177c6823093f4d1a9ac785e998

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



page-101-load-curves.png | SHA-256: 9f2a339ba61d022ee055d3b4ebd6eef03bd1653cff253d94d3607246d27991f0

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID T3YGDDG3I3AZ7TK3WJFEIZMJi6	SOURCE DOCUMENT ROTHE_ERDE_CATALOG_2023
SOURCE FILE Rothe Erde.pdf	SOURCE LOCATION PDF page 101 Printed page 196-197
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/rothe-erde/191-40-2800-990-41-1502/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.