

Factory-Verified Replacement

MERYDOM RKS.222605101001

Certified for interchange with SKF RKS.222605101001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKS.222605101001

REFERENCE

SKF RKS.222605101001

SERIES

SKF_ROLLER_CUSTOM_UNGEARED Series

STRUCTURE

Crossed Cylindrical Roller

OVERALL OD

1,144 mm

OVERALL ID

868 mm


OVERALL HEIGHT

100 mm

GEAR

Ungear

Published Technical Drawing



skf-p114-outline-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKS.222605101001
Certified interchangeable with	SKF RKS.222605101001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	M2RNF12LUZ66CHM4H5GTRDRJIS
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	SKF
Reference series	SKF_ROLLER_CUSTOM_UNGEARED Series
Reference model	RKS.222605101001
Bearing structure	Crossed Cylindrical Roller
Gear arrangement	Ungeared
DIMENSION	
Raceway diameter (dm)	980 mm
Overall outside diameter (D)	1,144 mm
Overall inside diameter (d)	868 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	100 mm
SKF catalogue dimension H1 (H1)	50 mm
SKF catalogue dimension D1 (D1)	1,088 mm
SKF catalogue dimension D2 (D2)	982 mm
SKF catalogue dimension C (C)	81 mm
SKF catalogue dimension C1 (C1)	68 mm
SKF catalogue dimension d1 (d1)	978 mm
SKF catalogue dimension d2 (d2)	870 mm
SKF catalogue dimension B (B)	88 mm
SKF catalogue dimension B1 (B1)	10 mm
Mass (Mass)	230 kg
PERFORMANCE	
Basic dynamic axial load rating (C)	607 kN
Basic static axial load rating (C0)	2,740 kN
PERFORMANCE RATINGS	
Basic Dynamic Axial	607 kN
Basic Static Axial	2,740 kN
MOUNTING INTERFACES	
Outer ring mounting	holes -
Inner ring mounting	holes -


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	SKF_SLEWING_BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
Source file	SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf
PDF page	114
Printed page	114
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	skf-p115-load-curve.webp SHA-256: 8d868a4f5288448d5310240a848a8ac7ee2292ad7b7b902bb5b2acb3725a7f91
Outline Drawing	skf-p114-outline-drawing.webp SHA-256: bfef483d68c3a2dc4e0286347f792d4c15a27134adc78525dc5bfb779d2b5f3a

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



skf-p115-load-curve.webp | SHA-256: 8d868a4f5288448d5310240a848a8ac7ee2292ad7b7b902bb5b2acb3725a7f91

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

M2RNF12LUZ66CHM4H5GTRDRJIS

SOURCE FILE

SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

SKF_SLEWING BEARINGS_PUB_BU_P2_06115_3_EN_2019_09

SOURCE LOCATION

PDF page 114 | Printed page 114

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/skf/rks-222605101001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.