

Factory-Verified Replacement

MERYDOM 1026E-01B-100


Certified for interchange with Tibet Makina 1026E-01B-100. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
1026E-01B-100	Tibet Makina 1026E-01B-100
SERIES	STRUCTURE
FOUR_POINT_EXTERNAL Series	Four-point contact ball
OVERALL OD	OVERALL ID
1,200 mm	910 mm
OVERALL HEIGHT	GEAR
110 mm	External gear

Published Technical Drawing



four_point_external-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	1026E-01B-100
Certified interchangeable with	Tibet Makina 1026E-01B-100
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	JHWCX5HBRO26EARX3VJZREL6PK
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Tibet Makina
Reference series	FOUR_POINT_EXTERNAL Series
Reference model	1026E-01B-100
Bearing structure	Four-point contact ball
Gear arrangement	External gear
DIMENSION	
Mass (Kg)	305 kg
Overall outside diameter (De)	1,200 mm
Overall inside diameter (Di)	910 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	110 mm
Outer ring height (He)	95 mm
Inner ring height (Hi)	95 mm
MOUNTING	
Outer ring bolt circle (Le)	1,098 mm
Inner ring bolt circle (Li)	954 mm
Outer ring mounting-hole count (ne)	36
Inner ring mounting-hole count (ni)	36
Outer ring mounting-hole specification (de)	24 mm
Inner ring mounting-hole specification (di)	24 mm
GEAR	
Gear module (m)	10 mm
Gear tooth count (z)	118
PERFORMANCE	
Normal tooth force (Ft_normal)	72 kN
Maximum tooth force (Ft_max)	144 kN
MISCELLANEOUS	
Raceway Pitch Diameter (DL)	1,026 mm
Lubrication Zerk Count (G)	4
PERFORMANCE RATINGS	
Rating Tooth Force Normal	72 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
Rating Tooth Force Max	144 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	36 holes - de 24 mm
Inner ring mounting	36 holes - di 24 mm
GEAR INTERFACE	
Pitch system	module
Module reference	10 mm
Number of teeth	118
SOURCE TRACEABILITY	
Source document code	TIBET_MAKINA_2015_CATALOG
Source file	tibet_makina_2015.pdf
PDF page	38
Printed page	38
Source language	TR-EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	four_point_external-static-load-curve.webp SHA-256: 426eaa3b8536155745593e633d891e075d05ebff2e6937c4f48a2b407d7d4e90
Outline Drawing	four_point_external-drawing.webp SHA-256: fab3f40746f3c0bd7981386d4c06ba1115cf219f3b2ef03fa0021620de6aac2f

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



four_point_external-static-load-curve.webp | SHA-256:
426eaa3b8536155745593e633d891e075d05ebff2e6937c4f48a2b407d7d4e90

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

JHWCX5HBRO26EARX3VJZREL6PK

SOURCE DOCUMENT

TIBET_MAKINA_2015_CATALOG

SOURCE FILE

tibet_makina_2015.pdf

SOURCE LOCATION

PDF page 38 | Printed page 38

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/tibet-makina/1026e-01b-100/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.