

Factory-Verified Replacement

MERYDOM E.1144.30.12.D.3-RV

Certified for interchange with Torriani Gianni E.1144.30.12.D.3-RV. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

E.1144.30.12.D.3-RV

REFERENCE

Torriani Gianni E.1144.30.12.D.3-RV

SERIES

E_30_45_50_D_R Series

STRUCTURE

Four-point contact ball

OVERALL OD

1,144 mm

OVERALL ID

870 mm


OVERALL HEIGHT

100 mm

GEAR

External gear

Published Technical Drawing



e_30_45_50_d_r-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	E.1144.30.12.D.3-RV
Certified interchangeable with	Torriani Gianni E.1144.30.12.D.3-RV
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	NFONUBI7WNZUUADPJUHVSZLHI
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Torriani Gianni
Reference series	E_30_45_50_D_R Series
Reference model	E.1144.30.12.D.3-RV
Bearing structure	Four-point contact ball
Gear arrangement	External gear
DIMENSION	
Overall outside diameter (Da)	1,144 mm
Torriani catalogue dimension U (U)	1,090 mm
Torriani catalogue dimension O (O)	993 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Di)	870 mm
Torriani catalogue dimension Ha (Ha)	84 mm
Torriani catalogue dimension Hb (Hb)	67 mm
Overall height (H)	100 mm
Mass (Kg)	230 kg
MOUNTING	
Outer ring bolt circle (La)	1,050 mm
Outer ring mounting-hole count (na)	SC
Outer ring mounting-hole specification (da)	22 mm
Inner ring bolt circle (Li)	910 mm
Inner ring mounting-hole count (ni)	SC
Inner ring mounting-hole specification (di)	22 mm
GEAR	
Gear pitch diameter (P)	1,122 mm
Gear module (m)	11 mm
Gear tooth count (z)	102
PERFORMANCE	
Normal tooth force (Fz_normal)	60 kN
Maximum tooth force (Fz_max)	120 kN
PERFORMANCE RATINGS	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
Rating Tooth Force Normal	60 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	120 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	holes - da 22 mm
Inner ring mounting	holes - di 22 mm
GEAR INTERFACE	
Pitch system	module
Module reference	11 mm
Number of teeth	102
SOURCE TRACEABILITY	
Source document code	TORRIANI_GIANNI_BALL_BEARINGS_CATALOG
Source file	catalogo-torriani-cuscinetti-a-sfere.pdf
PDF page	26
Printed page	26
Source language	IT-EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	e_30_45_50_d_r-static-load-curve.webp SHA-256: 84c21e8d0b13287fe3185d5b1177950cd5d90659a568c419de998196da9d13b0
Outline Drawing	e_30_45_50_d_r-drawing.webp SHA-256: c1455855782f5156b2ab765b670add23ffd342f00ac7ba983ebbe1d3943f526a

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



e_30_45_50_d_r-static-load-curve.webp | SHA-256:
84c21e8d0b13287fe3185d5b1177950cd5d90659a568c419de998196da9d13b0

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

NFONUBI7WNZUUADPJUHVSZLHI

SOURCE FILE

catalogo-torriani-cuscinetti-a-sfere
.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

TORRIANI_GIANNI_BALL_BEARINGS_CATALOG

SOURCE LOCATION

PDF page 26 | Printed page 26

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/products/slewing-bearing-replacements/torriani-gianni/e-1144-30-12-d-3-rv/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.