

Factory-Verified Replacement

MERYDOM 92-20 0741/1-07242

Certified for interchange with IMO 92-20 0741/1-07242.
This document consolidates the public product record,
complete published specifications, technical media,
source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle,
mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

92-20 0741/1-07242

REFERENCE

IMO 92-20 0741/1-07242

SERIES

920 Series

STRUCTURE

Rolamento de esferas com an is
flangeados

OVERALL OD

848 mm

OVERALL ID

648 mm


OVERALL HEIGHT

mm

GEAR

Engrenagem interna

Published Technical Drawing



imo-92200741107242-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	92-20 0741/1-07242
Certified interchangeable with	IMO 92-20 0741/1-07242
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	WA26JRWYI44JFDRLSMEVG2H4DQ
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	IMO
Reference series	920 Series
Reference model	92-20 0741/1-07242
Bearing structure	Rolamento de esferas com an is flangeados
Gear arrangement	Engrenagem interna
DIMENSION	
Overall outside diameter (Da)	848 mm
Overall inside diameter (di)	648 mm
Assembly weight (G)	52 kg

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MOUNTING	
Outer ring bolt circle (La)	820 mm
Outer ring mounting-hole count (na)	12
Inner ring bolt circle (Li)	705 mm
Inner ring mounting-hole count (ni)	20
GEAR	
Gear pitch diameter (d)	660 mm
Gear module (m)	6 mm
Gear tooth count (z)	110
PERFORMANCE	
Permitted circumferential force, normal (fz_norm)	17,5 kN
Permitted circumferential force, maximum (fz_max)	32,9 kN
Static radial load rating (Co_rad)	212 kN
Static axial load rating (Co_ax)	496 kN
Dynamic radial load rating (C_rad)	194 kN
Dynamic axial load rating (C_ax)	195 kN
PERFORMANCE RATINGS	
Fz Norm	17,5 kN Not simultaneous with other listed dynamic ratings
Fz Max	32,9 kN Not simultaneous with other listed dynamic ratings
Co Rad	212 kN Not simultaneous with other listed dynamic ratings
Co Ax	496 kN Not simultaneous with other listed dynamic ratings


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
C Rad	194 kN Not simultaneous with other listed dynamic ratings
C Ax	195 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	12 holes - See source drawing
Inner ring mounting	20 holes - See source drawing
GEAR INTERFACE	
Pitch system	module
Module reference	6 mm
Number of teeth	110
SOURCE TRACEABILITY	
Source document code	IMO_FLANGE_BALL_EN
Source file	imo_kugeldrehverbindung_mit_flanschring-en.pdf
PDF page	3
Printed page	Not published
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	imo-92200741107242-curve.webp SHA-256: 9eb3846cea7f731bd99e91eeff43b54af39d7cce067ebbb16bb0cf13ec394e60
Outline Drawing	imo-92200741107242-drawing.webp SHA-256: f02172cd47576197e27998d0b9dfad6edd07b8654087efb1ae5457428b487367

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Radial clearance: 0 - 0.3 mm
Axial tilting clearance: 0 - 0.5 mm
Bearing ring material: C45N
4 Taper type grease nipples on the circumference
Mounting holes equally spaced
Raceway system supplied pre-lubricated
Dimensions without tolerances DIN ISO 2768 coarse

imo-92200741107242-curve.webp | SHA-256: 9eb3846cea7f731bd99e91eeff43b54af39d7cce067ebbb16bb0cf13ec394e60

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

WA26JRWYI44JFDRLSMEVG2H4DQ

SOURCE DOCUMENT

IMO_FLANGE_BALL_EN

SOURCE FILE

**imo_kugeldrehverbindung_mit_flanschr
ing-en.pdf**

SOURCE LOCATION

**PDF page 3 | Printed page Not
published**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/imo/92-20-0741-1-07242/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.