

Factory-Verified Replacement

MERYDOM VLA 200944 N

Certified for interchange with INA VLA 200944 N. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

VLA 200944 N

SERIES

VLA 20 Series

OVERALL OD

1,046.1 mm

OVERALL HEIGHT

mm

REFERENCE

INA VLA 200944 N

STRUCTURE

Esferas de contato de quatro pontos


OVERALL ID

834 mm

GEAR

Engrenagem externa

Published Technical Drawing



## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| MERYDOM CERTIFIED PRODUCT            |                                        |
|--------------------------------------|----------------------------------------|
| Product brand                        | MERYDOM                                |
| MERYDOM model                        | VLA 200944 N                           |
| Certified interchangeable with       | INA VLA 200944 N                       |
| Verification status                  | Level 3 - MERYDOM Engineering Verified |
| Reviewed by                          | MERYDOM Engineering Department         |
| Public record UID                    | LDDA4RFJTMSM5JHOPOSJOVEFHA             |
| MATERIALS                            |                                        |
| Configurable ring material options   | 42CrMo / 50Mn                          |
| Seal material                        | NBR - Nitrile rubber                   |
| Configurable spacer material options | Engineering nylon / Brass              |
| IDENTIFICATION                       |                                        |
| Reference brand                      | INA                                    |
| Reference series                     | VLA 20 Series                          |
| Reference model                      | VLA 200944 N                           |
| Bearing structure                    | Esferas de contato de quatro pontos    |
| Gear arrangement                     | Engrenagem externa                     |
| DIMENSION                            |                                        |
| Mass (Mass)                          | 71,5 kg                                |
| Overall outside diameter (Da)        | 1.046,1 mm                             |
| Overall inside diameter (di)         | 834+0,7 mm                             |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| DIMENSION (CONTINUED)                     |              |
|-------------------------------------------|--------------|
| Inside centring diameter (diZT)           | 836 mm       |
| Catalog diameter Di (Di)                  | 945,5+0,7 mm |
| Catalog centring diameter DiZT (DiZT)     | 947 mm       |
| Catalog diameter da (da)                  | 942,5-0,7 mm |
| MOUNTING                                  |              |
| Outer ring bolt circle (La)               | 985 mm       |
| Outer ring mounting-hole count (na)       | 20           |
| Inner ring bolt circle (Li)               | 862 mm       |
| Inner ring mounting-hole count (ni)       | 20           |
| GEAR                                      |              |
| Gear pitch diameter (d0)                  | 1.032 mm     |
| Gear module (m)                           | 8 mm         |
| Gear tooth count (z)                      | 129          |
| PERFORMANCE                               |              |
| Maximum permissible radial load (Fr perm) | 82,6 kN      |
| Normal tooth force (Fznorm)               | 28,3 kN      |
| Maximum tooth force (Fzmax)               | 42 kN        |
| Basic dynamic axial load rating (Ca)      | 231 kN       |
| Basic static axial load rating (C0a)      | 670 kN       |
| Basic dynamic radial load rating (Cr)     | 151 kN       |

## Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

| PERFORMANCE (CONTINUED)                            |                                                              |
|----------------------------------------------------|--------------------------------------------------------------|
| Basic static radial load rating (C <sub>0r</sub> ) | 250 kN                                                       |
| PERFORMANCE RATINGS                                |                                                              |
| Rating Radial Static                               | 250 kN   Not simultaneous with other listed dynamic ratings  |
| Rating Axial Static                                | 670 kN   Not simultaneous with other listed dynamic ratings  |
| Rating Radial Dynamic                              | 151 kN   Not simultaneous with other listed dynamic ratings  |
| Rating Axial Dynamic                               | 231 kN   Not simultaneous with other listed dynamic ratings  |
| Rating Tooth Force Max                             | 42 kN   Not simultaneous with other listed dynamic ratings   |
| Rating Tooth Force Normal                          | 28,3 kN   Not simultaneous with other listed dynamic ratings |
| Rating Radial Load Max                             | 82,6 kN   Not simultaneous with other listed dynamic ratings |
| MOUNTING INTERFACES                                |                                                              |
| Outer ring mounting                                | 20 holes - See source drawing                                |
| Inner ring mounting                                | 20 holes - See source drawing                                |
| GEAR INTERFACE                                     |                                                              |
| Pitch system                                       | module                                                       |
| Module reference                                   | 8 mm                                                         |
| Number of teeth                                    | 129                                                          |
| SOURCE TRACEABILITY                                |                                                              |
| Source document code                               | INA-SLEWING-RINGS-CATALOGUE-404-2012                         |
| Source file                                        | 404_de_en_1.pdf                                              |
| PDF page                                           | 54                                                           |


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.


| SOURCE TRACEABILITY (CONTINUED) |                                                                                                          |
|---------------------------------|----------------------------------------------------------------------------------------------------------|
| Printed page                    | 52                                                                                                       |
| Source language                 | EN-DE                                                                                                    |
| Original unit system            | Metric                                                                                                   |
| PUBLISHED TECHNICAL MEDIA       |                                                                                                          |
| Load Curve Chart                | ina-g01-curve.webp   SHA-256:<br>2caac1c864b5 added53bd9d1e31436acf09dda1d167c8ac24282b1df9f2a<br>a9c8cf |
| Outline Drawing                 | ina-g01-drawing.webp   SHA-256:<br>e338fcc82ad5e0dba14b2ecf00b36a89b66bda6f2920b5ecee24fa2aa6<br>adb292  |

## Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



Static limiting load diagram



Static limiting load diagram

ina-g01-curve.webp | SHA-256: 2caac1c864b5fdd53bd9d1e31436acf09dda1d167c8ac24282b1df9f2aa9c8cf

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

## Source and Verification Traceability

**PUBLIC RECORD UID****LDDA4RFJTMSM5JHOPOSJOVEFHA****SOURCE DOCUMENT****INA-SLEWING-RINGS-CATALOGUE-404-2012****SOURCE FILE****404\_de\_en\_1.pdf****SOURCE LOCATION****PDF page 54 | Printed page 52****VERIFICATION****Level 3 - MERYDOM Engineering  
Verified****REVIEWED BY****MERYDOM Engineering Department**

## Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

### Request Price, Delivery and Final Engineering Confirmation

Email: [jovi@merydom.com](mailto:jovi@merydom.com) | Email: [andi@merydom.com](mailto:andi@merydom.com) | WhatsApp: +86 17705201170Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/ina/vla-200944-n/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.