

Factory-Verified Replacement

MERYDOM 16274001

Certified for interchange with Kaydon 16274001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16274001

REFERENCE

Kaydon 16274001

SERIES

DT Series

STRUCTURE

Esferas de contato de oito pontos

OVERALL OD

1,440.002 mm

OVERALL ID

1,108.989 mm

OVERALL HEIGHT

138.989 mm

GEAR

Engrenagem interna

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16274001
Certified interchangeable with	Kaydon 16274001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	FBLBMDCJL4Y6X3ACNMPRDTVUR
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	DT Series
Reference model	16274001
Bearing structure	Esferas de contato de oito pontos
Gear arrangement	Engrenagem interna
DIMENSION	
Overall outside diameter (Do)	56.693 in Metric reference: aproximadamente 1.440 mm
Overall inside diameter (di)	43.661 in Metric reference: aproximadamente 1.108,99 mm
Inner ring body ID (dr)	46.142 in Metric reference: aproximadamente 1.172,01 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	5.472 in Metric reference: aproximadamente 138,99 mm
Assembly weight (G)	1200 lb Metric reference: aproximadamente 544,311 kg
MOUNTING	
Outer ring bolt circle (Lo)	54.724 in Metric reference: aproximadamente 1.389,99 mm
Inner ring bolt circle (Li)	48.425 in Metric reference: aproximadamente 1.230 mm
GEAR	
Gear pitch diameter (D2)	44.094 in Metric reference: aproximadamente 1.119,99 mm
Gear tooth count (z2)	80
PERFORMANCE	
Maximum gear tooth load (Fz)	48640 lbf Metric reference: aproximadamente 216,36 kN
Moment load rating (Crm)	1225400 ft lbf Metric reference: aproximadamente 1.661,42 kN m
PERFORMANCE RATINGS	
Moment	1225400.0000000000 ft lbf Metric reference: aproximadamente 1.661,42 kN m
Gear Tooth	48640.0000000000 lbf Metric reference: aproximadamente 216,36 kN
MOUNTING INTERFACES	
Outer ring mounting	48 holes - 0.866
Inner ring mounting	48 holes - 0.866
GEAR INTERFACE	
Pitch system	MODULE
Module reference	14 mm
Number of teeth	80

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	90
Printed page	88
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID FBLBMDCJL4Y6X3ACNMPRDTVUR	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 90 Printed page 88
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/16274001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.