

Factory-Verified Replacement

MERYDOM 16315001

Certified for interchange with Kaydon 16315001. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

16315001

REFERENCE

Kaydon 16315001

SERIES

XT Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

4,320.007 mm

OVERALL ID

3,729.99 mm

OVERALL HEIGHT

153.01 mm

GEAR

Engrenagem externa

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	16315001
Certified interchangeable with	Kaydon 16315001
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	3PQRZQE45R65J7MI7V7B5YZADI
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	XT Series
Reference model	16315001
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Do)	170.079 in Metric reference: aproximadamente 4.320,01 mm
Overall inside diameter (di)	146.850 in Metric reference: aproximadamente 3.730 mm
Overall height (H)	6.024 in Metric reference: aproximadamente 153,01 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	8030 lb Metric reference: aproximadamente 3.642,347 kg
MOUNTING	
Outer ring bolt circle (Lo)	162.598 in Metric reference: aproximadamente 4.129,99 mm
Inner ring bolt circle (Li)	150.787 in Metric reference: aproximadamente 3.829,99 mm
GEAR	
Gear pitch diameter (D2)	168.504 in Metric reference: aproximadamente 4.280 mm
Gear tooth count (z2)	214
PERFORMANCE	
Maximum gear tooth load (Fz)	80500 lbf Metric reference: aproximadamente 358,08 kN
Moment load rating (Crm)	4176000 ft lbf Metric reference: aproximadamente 5.661,9 kN m
PERFORMANCE RATINGS	
Moment	4176000.0000000000 ft lbf Metric reference: aproximadamente 5.661,9 kN m
Gear Tooth	80500.0000000000 lbf Metric reference: aproximadamente 358,08 kN
MOUNTING INTERFACES	
Outer ring mounting	72 holes - 1.535
Inner ring mounting	72 holes - 1.535
GEAR INTERFACE	
Pitch system	MODULE
Module reference	20 mm
Number of teeth	214
SOURCE TRACEABILITY	

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	82
Printed page	80
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID 3PQRZQE45R65J7MI7V7B5YZADI	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 82 Printed page 80
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/16315001/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.