

Factory-Verified Replacement

MERYDOM HS6-37N1Z

Certified for interchange with Kaydon HS6-37N1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

HS6-37N1Z

REFERENCE

Kaydon HS6-37N1Z

SERIES

HS Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

1,047.75 mm

OVERALL ID

841.578 mm

OVERALL HEIGHT

55.88 mm

GEAR

Engrenagem interna

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	HS6-37N1Z
Certified interchangeable with	Kaydon HS6-37N1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	ZLZQYWXSXI5SDH5I6DLVDKSMXX
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	HS Series
Reference model	HS6-37N1Z
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem interna
DIMENSION	
Overall outside diameter (Do)	41.250 in Metric reference: aproximadamente 1.047,8 mm
Overall inside diameter (di)	33.133 in Metric reference: aproximadamente 841,58 mm
Overall height (H)	2.200 in Metric reference: aproximadamente 56 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	226 lb Metric reference: aproximadamente 102,512 kg
MOUNTING	
Outer ring bolt circle (Lo)	39.750 in Metric reference: aproximadamente 1.009,7 mm
Inner ring bolt circle (Li)	35.500 in Metric reference: aproximadamente 902 mm
GEAR	
Gear pitch diameter (D2)	33.667 in Metric reference: aproximadamente 855,14 mm
Diametral pitch (Pd)	3
Gear tooth count (z2)	101
PERFORMANCE	
Maximum gear tooth load (Fz)	7531 lbf Metric reference: aproximadamente 33,5 kN
Moment load rating (Crm)	130900 ft lbf Metric reference: aproximadamente 177,48 kN m
PERFORMANCE RATINGS	
Moment	130900.0000000000 ft lbf Metric reference: aproximadamente 177,48 kN m
Gear Tooth	7531.0000000000 lbf Metric reference: aproximadamente 33,5 kN
MOUNTING INTERFACES	
Outer ring mounting	18 holes - 0.688 through, equally spaced
Inner ring mounting	32 holes - 0.500-13 UNC-2B; 0.750 min full thread
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	3 DP
Module reference	8.466667 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Number of teeth	101
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	56
Printed page	54
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID ZLZQYWXSXI5SDH5I6DLVDKSMMX	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 56 Printed page 54
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/hs6-37n1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.