

Factory-Verified Replacement

MERYDOM MTE-470T

Certified for interchange with Kaydon MTE-470T. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

MTE-470T

REFERENCE

Kaydon MTE-470T

SERIES

MT Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

683.26 mm

OVERALL ID

469.9 mm

OVERALL HEIGHT

60.325 mm

GEAR

Engrenagem externa

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	MTE-470T
Certified interchangeable with	Kaydon MTE-470T
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	6HFEUWVZXJDY76GWEZ6XFGYVGP
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	MT Series
Reference model	MTE-470T
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Do)	26.900 in Metric reference: aproximadamente 683 mm
Overall inside diameter (di)	18.500 in Metric reference: aproximadamente 470 mm
Overall height (H)	2.375 in Metric reference: aproximadamente 60,33 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	147 lb Metric reference: aproximadamente 66,678 kg
MOUNTING	
Outer ring bolt circle (Lo)	24.500 in Metric reference: aproximadamente 622 mm
Inner ring bolt circle (Li)	20.000 in Metric reference: aproximadamente 508 mm
GEAR	
Gear pitch diameter (D2)	26.500 in Metric reference: aproximadamente 673 mm
Diametral pitch (Pd)	4
Gear tooth count (z2)	106
PERFORMANCE	
Maximum gear tooth load (Fz)	10460 lbf Metric reference: aproximadamente 46,53 kN
Moment load rating (Crm)	191600 ft lbf Metric reference: aproximadamente 259,77 kN m
PERFORMANCE RATINGS	
Moment	191600.0000000000 ft lbf Metric reference: aproximadamente 259,77 kN m
Gear Tooth	10460.0000000000 lbf Metric reference: aproximadamente 46,53 kN
MOUNTING INTERFACES	
Outer ring mounting	18 holes - 3/4-10
Inner ring mounting	24 holes - 3/4-10
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	4 DP
Module reference	6.35 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Number of teeth	106
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	68
Printed page	66
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID 6HFEUWVZXJDY76GWEZ6XFGYVGP	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 68 Printed page 66
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/mte-470t/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.