

Factory-Verified Replacement

MERYDOM MTE-730

Certified for interchange with Kaydon MTE-730. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

MTE-730

REFERENCE

Kaydon MTE-730

SERIES

MT Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

1,062.99 mm

OVERALL ID

730.25 mm

OVERALL HEIGHT

82.55 mm

GEAR

Engrenagem externa

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	MTE-730
Certified interchangeable with	Kaydon MTE-730
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	G5BRV43JFZ2ZPWY7MPVVPUBEOF
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	MT Series
Reference model	MTE-730
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Do)	41.85 in Metric reference: aproximadamente 1.063 mm
Overall inside diameter (di)	28.750 in Metric reference: aproximadamente 730,3 mm
Overall height (H)	3.250 in Metric reference: aproximadamente 82,6 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	491 lb Metric reference: aproximadamente 222,714 kg
MOUNTING	
Outer ring bolt circle (Lo)	38.000 in Metric reference: aproximadamente 965 mm
Inner ring bolt circle (Li)	31.00 in Metric reference: aproximadamente 787 mm
GEAR	
Gear pitch diameter (D2)	41.200 in Metric reference: aproximadamente 1.046 mm
Diametral pitch (Pd)	2,5
Gear tooth count (z2)	103
PERFORMANCE	
Maximum gear tooth load (Fz)	21290 lbf Metric reference: aproximadamente 94,7 kN
Moment load rating (Crm)	588000 ft lbf Metric reference: aproximadamente 797,22 kN m
PERFORMANCE RATINGS	
Moment	588000.0000000000 ft lbf Metric reference: aproximadamente 797,22 kN m
Gear Tooth	21290.0000000000 lbf Metric reference: aproximadamente 94,7 kN
MOUNTING INTERFACES	
Outer ring mounting	20 holes - 1.063
Inner ring mounting	24 holes - 1.063
GEAR INTERFACE	
Pitch system	DP
Diametral pitch	2.5 DP
Module reference	10.16 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Number of teeth	103
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	68
Printed page	66
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID G5BRV43JFZ2ZPWY7MPVVPUBEOF	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 68 Printed page 66
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/mte-730/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.