

Factory-Verified Replacement

MERYDOM MTO-065T

Certified for interchange with Kaydon MTO-065T. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

MTO-065T

REFERENCE

Kaydon MTO-065T

SERIES

MT Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

135.001 mm

OVERALL ID

64.999 mm

OVERALL HEIGHT

21.996 mm

GEAR

Sem engrenagem

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	MTO-065T
Certified interchangeable with	Kaydon MTO-065T
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	YMB3TMPCYE6JW5QUISI4NG2GYG
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	MT Series
Reference model	MTO-065T
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Sem engrenagem
DIMENSION	
Overall outside diameter (Do)	5.315 in Metric reference: aproximadamente 135 mm
Overall inside diameter (di)	2.559 in Metric reference: aproximadamente 65 mm
Overall height (H)	0.866 in Metric reference: aproximadamente 22 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Assembly weight (G)	4 lb Metric reference: aproximadamente 1,814 kg
MOUNTING	
Outer ring bolt circle (Lo)	4.724 in Metric reference: aproximadamente 119,99 mm
Inner ring bolt circle (Li)	3.149 in Metric reference: aproximadamente 79,98 mm
PERFORMANCE	
Moment load rating (Crm)	1075 ft lbf Metric reference: aproximadamente 1,46 kN m
PERFORMANCE RATINGS	
Moment	1075.0000000000 ft lbf Metric reference: aproximadamente 1,46 kN m
MOUNTING INTERFACES	
Outer ring mounting	8 holes - M8
Inner ring mounting	8 holes - M8
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	66
Printed page	64
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID

YMB3TMPCYE6JW5QUISI4NG2GYG

SOURCE DOCUMENT

KAYDON-CAT390

SOURCE FILE

Kaydon_Catalog_390.pdf

SOURCE LOCATION

PDF page 66 | Printed page 64

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1
- Confirm the exact model designation and all installation-envelope dimensions.
- 2
- Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3
- Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4
- Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5
- Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6
- Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/mto-065t/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.