

Factory-Verified Replacement

MERYDOM RK6-22P1Z

Certified for interchange with Kaydon RK6-22P1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RK6-22P1Z

REFERENCE

Kaydon RK6-22P1Z

SERIES

RK Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

647.954 mm

OVERALL ID

434.086 mm

OVERALL HEIGHT

56.007 mm

GEAR

Sem engrenagem

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RK6-22P1Z
Certified interchangeable with	Kaydon RK6-22P1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	ULA3NOXLRXGKOFU5WHSKSLX2
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	RK Series
Reference model	RK6-22P1Z
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Sem engrenagem
DIMENSION	
Overall outside diameter (Do)	25.510 in Metric reference: aproximadamente 648 mm
Overall inside diameter (di)	17.090 in Metric reference: aproximadamente 434,1 mm
Outer ring body OD (Dr)	22.990 in Metric reference: aproximadamente 583,9 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Outer ring inner diameter (Di)	21.340 in Metric reference: aproximadamente 542 mm
Inner ring outer diameter (do)	21.260 in Metric reference: aproximadamente 540 mm
Inner ring body ID (dr)	19.610 in Metric reference: aproximadamente 498,1 mm
Overall height (H)	2.205 in Metric reference: aproximadamente 56,01 mm
Assembly weight (G)	76 lb Metric reference: aproximadamente 34,473 kg
MOUNTING	
Outer ring bolt circle (Lo)	24.380 in Metric reference: aproximadamente 619,3 mm
Inner ring bolt circle (Li)	18.130 in Metric reference: aproximadamente 460,5 mm
PERFORMANCE	
Moment load rating (Crm)	37700 ft lbf Metric reference: aproximadamente 51,11 kN m
PERFORMANCE RATINGS	
Moment	37700.0000000000 ft lbf Metric reference: aproximadamente 51,11 kN m
MOUNTING INTERFACES	
Outer ring mounting	12 holes - 0.688 through, equally spaced
Inner ring mounting	15 holes - 0.688 through, equally spaced
GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	50

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Printed page	48
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID ULA3NOXLRXGKOFU5WHSKSLX2	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 50 Printed page 48
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/rk6-22p1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.