

Factory-Verified Replacement

MERYDOM RK6-33E1Z

Certified for interchange with Kaydon RK6-33E1Z. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RK6-33E1Z

REFERENCE

Kaydon RK6-33E1Z

SERIES

RK Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

944.88 mm

OVERALL ID

734.06 mm

OVERALL HEIGHT

56.007 mm

GEAR

Engrenagem externa

No public model drawing is attached to this record. Submit the application and required interface format for final drawing confirmation.

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RK6-33E1Z
Certified interchangeable with	Kaydon RK6-33E1Z
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	MDS6X4X5JPNTMVDFTZST4FBVNM
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Kaydon
Reference series	RK Series
Reference model	RK6-33E1Z
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Do)	37.200 in Metric reference: aproximadamente 945 mm
Overall inside diameter (di)	28.900 in Metric reference: aproximadamente 734 mm
Outer ring inner diameter (Di)	33.150 in Metric reference: aproximadamente 842 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Inner ring outer diameter (do)	33.070 in Metric reference: aproximadamente 840 mm
Inner ring body ID (dr)	31.420 in Metric reference: aproximadamente 798,1 mm
Overall height (H)	2.205 in Metric reference: aproximadamente 56,01 mm
Assembly weight (G)	152 lb Metric reference: aproximadamente 68,946 kg
MOUNTING	
Outer ring bolt circle (Lo)	35.000 in Metric reference: aproximadamente 889 mm
Inner ring bolt circle (Li)	30.000 in Metric reference: aproximadamente 762 mm
GEAR	
Gear pitch diameter (D2)	36.667 in Metric reference: aproximadamente 931,34 mm
Diametral pitch (Pd)	3
Gear tooth count (z2)	110
PERFORMANCE	
Maximum gear tooth load (Fz)	7580 lbf Metric reference: aproximadamente 33,72 kN
Moment load rating (Crm)	56500 ft lbf Metric reference: aproximadamente 76,6 kN m
PERFORMANCE RATINGS	
Moment	56500.0000000000 ft lbf Metric reference: aproximadamente 76,6 kN m
Gear Tooth	7580.0000000000 lbf Metric reference: aproximadamente 33,72 kN
MOUNTING INTERFACES	
Outer ring mounting	18 holes - 0.500-13 UNC-2B; 0.750 min full thread; equally spaced
Inner ring mounting	18 holes - 0.688 through, equally spaced

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Pitch system	DP
Diametral pitch	3 DP
Module reference	8.466667 mm
Number of teeth	110
SOURCE TRACEABILITY	
Source document code	KAYDON-CAT390
Source file	Kaydon_Catalog_390.pdf
PDF page	52
Printed page	50
Source language	EN-US
Original unit system	Inch

Source and Verification Traceability

PUBLIC RECORD UID MDS6X4X5JPNTMVDFTZST4FBVNM	SOURCE DOCUMENT KAYDON-CAT390
SOURCE FILE Kaydon_Catalog_390.pdf	SOURCE LOCATION PDF page 52 Printed page 50
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/kaydon/rk6-33e1z/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.