

Factory-Verified Replacement

MERYDOM KUD02106-050WJ15-900-000

Certified for interchange with Liebherr KUD02106-050WJ15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

KUD02106-050WJ15-900-000

REFERENCE

Liebherr KUD02106-050WJ15-900-000

SERIES

KUD_50_WJ Series

STRUCTURE

Esferas de contato de quatro pontos de duas carreiras

OVERALL OD

2,285 mm

OVERALL ID

1,850.8 mm


OVERALL HEIGHT

184 mm

GEAR

Engrenagem interna

Published Technical Drawing



liebherr-page-121-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	KUD02106-050WJ15-900-000
Certified interchangeable with	Liebherr KUD02106-050WJ15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	ANVES4QWPWR5LKQLCYR4RMMZ5U
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	KUD_50_WJ Series
Reference model	KUD02106-050WJ15-900-000
Bearing structure	Esferas de contato de quatro pontos de duas carreiras
Gear arrangement	Engrenagem interna
DIMENSION	
Mass (Weight)	1.564 kg
Overall outside diameter (Da)	2.285 mm
Overall inside diameter (Di)	1.850,8 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	184 mm
Liebherr catalogue dimension O (O)	2.104 mm
Liebherr catalogue dimension U (U)	2.108 mm
Liebherr catalogue dimension H1 (H1)	172 mm
Liebherr catalogue dimension H2 (H2)	172 mm
MOUNTING	
Outer ring bolt circle (La)	2.213 mm
Inner ring bolt circle (Li)	1.996 mm
La/Li mounting-hole count (n)	60
Mounting fastener specification (M)	33
Liebherr catalogue count n1 (n1)	8
GEAR	
Gear pitch diameter (d)	1.862 mm
Gear module (m)	14 mm
Gear tooth count (z)	133
Addendum modification product x^*m (x^*m)	-7 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-1,4 mm
Gear face width (b)	140 mm
PERFORMANCE	
Standard tooth force (Fz standard)	170,4 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	340,9 kN
Static load rating (Cstat)	30.608 kN
Dynamic load rating (Cdyn)	2.016 kN
PERFORMANCE RATINGS	
Rating Dynamic	2.016 kN Not simultaneous with other listed dynamic ratings
Rating Static	30.608 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	340,9 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	170,4 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	60 holes - 33
Inner ring mounting	60 holes - 33
GEAR INTERFACE	
Pitch system	module
Module reference	14 mm
Number of teeth	133
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	121
Printed page	121


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-121-curve.webp SHA-256: 2dc8dfb288174cb0a96eda538a3ad1d421732594d9e230e9eceb82c95a4b5711
Outline Drawing	liebherr-page-121-drawing.webp SHA-256: 7a4f077302a95dbccda0852085cdf09bf93e96eb8a06287be4cfae985a89466e

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-121-curve.webp | SHA-256: 2dc8dfb288174cb0a96eda538a3ad1d421732594d9e230e9eceb82c95a4b5711

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

ANVES4QWPWR5LKQLCYR4RMMZ5U

SOURCE FILE

liebherr-slewing-bearings-product-ca
talogue-pt-metric-web.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA
TALOGUE-2018

SOURCE LOCATION

PDF page 121 | Printed page 121

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:

<https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/liebherr/kud02106-050wj15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.