

Factory-Verified Replacement

MERYDOM ROD03150-050DA15-900-000


Certified for interchange with Liebherr ROD03150-050DA15-900-000. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL	REFERENCE
ROD03150-050DA15-900-000	Liebherr ROD03150-050DA15-900-000
SERIES	STRUCTURE
ROD_50_DA Series	Rolos de tr s carreiras
OVERALL OD	OVERALL ID
3,571.2 mm	2,885 mm
OVERALL HEIGHT	GEAR
268 mm	Engrenagem externa

Published Technical Drawing



liebherr-page-140-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	ROD03150-050DA15-900-000
Certified interchangeable with	Liebherr ROD03150-050DA15-900-000
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	QG4BPCPUSCMSF6CDUTSYTYNOCU
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Liebherr
Reference series	ROD_50_DA Series
Reference model	ROD03150-050DA15-900-000
Bearing structure	Rolos de tr s carreiras
Gear arrangement	Engrenagem externa
DIMENSION	
Mass (Weight)	5.298 kg
Overall outside diameter (Da)	3.571,2 mm
Overall inside diameter (Di)	2.885 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall height (H)	268 mm
Liebherr catalogue dimension O (O)	3.210 mm
Liebherr catalogue dimension U (U)	3.196 mm
Liebherr catalogue dimension H1 (H1)	203 mm
Liebherr catalogue dimension H2 (H2)	258 mm
MOUNTING	
Outer ring bolt circle (La)	3.350 mm
Inner ring bolt circle (Li)	2.975 mm
La/Li mounting-hole count (n)	48
Mounting fastener specification (M)	42
Liebherr catalogue count n1 (n1)	8
GEAR	
Gear pitch diameter (d)	3.504 mm
Gear module (m)	24 mm
Gear tooth count (z)	146
Addendum modification product x^*m (x^*m)	12 mm
Liebherr catalogue gear dimension k^*m (k^*m)	-2,4 mm
Gear face width (b)	203 mm
PERFORMANCE	
Standard tooth force (Fz standard)	423,6 kN

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Maximum tooth force (Fz maximum)	847,2 kN
Static load rating (Cstat)	58.080 kN
Dynamic load rating (Cdyn)	6.544 kN
PERFORMANCE RATINGS	
Rating Dynamic	6.544 kN Not simultaneous with other listed dynamic ratings
Rating Static	58.080 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	847,2 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Standard	423,6 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	48 holes - 42
Inner ring mounting	48 holes - 42
GEAR INTERFACE	
Pitch system	module
Module reference	24 mm
Number of teeth	146
SOURCE TRACEABILITY	
Source document code	LIEBHERR-SLEWING-BEARINGS-PRODUCT-CATALOGUE-2018
Source file	liebherr-slewing-bearings-product-catalogue-pt-metric-web.pdf
PDF page	140
Printed page	140


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source language	EN
Original unit system	Mixed_metric_dp_threads
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	liebherr-page-140-curve.webp SHA-256: 0c65cc461bef30e426aaeabd1cabef81532429eaaecfb564ee8f935e5d dd668d
Outline Drawing	liebherr-page-140-drawing.webp SHA-256: dce2e2500a3daa3838b8ca5cdd27994184301f3b96c333e0288bb3af5f 2e59cb

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



liebherr-page-140-curve.webp | SHA-256: 0c65cc461bef30e426aaebd1cabef81532429eaaecfb564ee8f935e5ddd668d

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

QG4BPCPUSCMSF6CDUTSYTYNOCU

SOURCE FILE

**liebherr-slewing-bearings-product-ca
talogue-pt-metric-web.pdf**

VERIFICATION

**Level 3 - MERYDOM Engineering
Verified**

SOURCE DOCUMENT

**LIEBHERR-SLEWING-BEARINGS-PRODUCT-CA
TALOGUE-2018**

SOURCE LOCATION

PDF page 140 | Printed page 140

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:

<https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/liebherr/rod03150-050da15-900-000/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.