

Factory-Verified Replacement

MERYDOM 08-0675-00

Certified for interchange with ROLLIX 08-0675-00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL
08-0675-00

SERIES
08 Series

OVERALL OD
816 mm

OVERALL HEIGHT
90 mm


REFERENCE
ROLLIX 08-0675-00

STRUCTURE
Rolos cruzados de uma carreira

OVERALL ID
573 mm

GEAR
Sem engrenagem

Published Technical Drawing



rollix-page-109-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	08-0675-00
Certified interchangeable with	ROLLIX 08-0675-00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	VLM3HNE5PPESENMPGNH3EUXVRY
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	08 Series
Reference model	08-0675-00
Bearing structure	Rolos cruzados de uma carreira
Gear arrangement	Sem engrenagem
DIMENSION	
Overall height (HT)	90 mm
Overall outside diameter (Dia De)	816 mm
Outer ring height (He)	73 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Dia Di)	573 mm
Inner ring height (Hi)	70 mm
Assembly weight (Weight)	137 kg
MOUNTING	
Outer ring pilot diameter (Dia Ce)	682 mm
Inner ring pilot diameter (Dia Ci)	574 mm
Outer ring hole type (External ring hole type)	Th
Outer ring bolt circle (Dia Fe)	753 mm
Outer ring mounting-hole count (Ne)	18
Outer ring mounting-hole specification (Dhe)	22 mm
Inner ring hole type (Inner ring hole type)	Th
Inner ring bolt circle (Dia Fi)	604 mm
Inner ring mounting-hole count (Ni)	18
Inner ring mounting-hole specification (Dhi)	22 mm
MISCELLANEOUS	
Ring with greasing holes (Ring with greasing holes)	E+I
Greasing hole type (Greasing hole type)	F+R
MOUNTING INTERFACES	
Outer ring mounting	18 holes - External ring hole type Th; Dhe 22 mm
Inner ring mounting	18 holes - Inner ring hole type Th; Dhi 22 mm


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	109
Printed page	109
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-109-curve.webp SHA-256: d787da237ebc5bacd998731201a191fb08bfb74fcf80b37c2c54f515f2 afeb92
Outline Drawing	rollix-page-109-drawing.webp SHA-256: f7e1205a7f4f0a671a2a141973e0dd903a08e1e3e930dcc91d1260191c 7512e5

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-109-curve.webp | SHA-256: d787da237ebc5bacd998731201a191fb08bfb74fcf80b37c2c54f515f2afeb92

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID VLM3HNE5PPESENMPGNH3EUXVRY	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 109 Printed page 109
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/rollix/08-0675-00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.