

Factory-Verified Replacement

MERYDOM 46-0944-00

Certified for interchange with ROLLIX 46-0944-00. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

46-0944-00

REFERENCE

ROLLIX 46-0944-00

SERIES

46 Series

STRUCTURE

Rolamento de rolos de precis o

OVERALL OD

1,046 mm

OVERALL ID

872 mm


OVERALL HEIGHT

56 mm

GEAR

Engrenagem externa

Published Technical Drawing



rollix-page-120-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	46-0944-00
Certified interchangeable with	ROLLIX 46-0944-00
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	YZWCU54IY4C7RH6ON7PV3E7TIY
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	ROLLIX
Reference series	46 Series
Reference model	46-0944-00
Bearing structure	Rolamento de rolos de precis o
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Dia De)	1.046 mm
Overall inside diameter (Dia Di)	872 mm
Overall height (HT)	56 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Outer ring height (He)	44 mm
Inner ring height (Hi)	44 mm
Assembly weight (Weight)	77 kg
MOUNTING	
Outer ring pilot diameter (Dia Ce)	947 mm
Inner ring pilot diameter (Dia Ci)	874 mm
Outer ring pilot height (Hce)	10 mm
Inner ring pilot height (Hci)	10 mm
Outer ring bolt circle (Fe)	985 mm
Outer ring mounting-hole count (Ne*)	40
Inner ring bolt circle (Fi)	898 mm
Inner ring mounting-hole count (Ni*)	44
GEAR	
Gear module (Module)	8 mm
Gear tooth count (Number of teeth)	129
Gear run-out (Gear run-out)	0,16 mm
PERFORMANCE	
Outer ring axial run-out (BE (ARO))	60 um
Inner ring axial run-out (BI (ARO))	60 um
Outer ring radial run-out (BE (RRO))	90 um

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE (CONTINUED)	
Inner ring radial run-out (BI (RRO))	90 um
Maximum unloaded starting torque (Maximum starting torque)	140 Nm
Maximum allowable rotation speed (Maximum allowable speed)	37 rpm
Static gear resistance (Static Gear Resistance)	53 kN
PERFORMANCE RATINGS	
Rating Starting Torque Max	140 Nm Not simultaneous with other listed dynamic ratings
Axial Runout Outer	60 um Not simultaneous with other listed dynamic ratings
Axial Runout Inner	60 um Not simultaneous with other listed dynamic ratings
Rating Speed Max	37 rpm Not simultaneous with other listed dynamic ratings
Radial Runout Outer	90 um Not simultaneous with other listed dynamic ratings
Radial Runout Inner	90 um Not simultaneous with other listed dynamic ratings
Rating Gear Static Resistance	53 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	40 holes - See source drawing
Inner ring mounting	44 holes - Hci 10 mm
GEAR INTERFACE	
Pitch system	module
Module reference	8 mm
Number of teeth	129
SOURCE TRACEABILITY	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

SOURCE TRACEABILITY (CONTINUED)	
Source document code	ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
Source file	ROLLIX.pdf
PDF page	120
Printed page	120
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	rollix-page-120-curve.webp SHA-256: 8db3c72c4d15922ba22691da5940bde446bb831dd20545f70889fbe8d4f5f9e2
Outline Drawing	rollix-page-120-drawing.webp SHA-256: 63c4c31735402a19635e964df03a84764c8d8e4cfc2e4426d19fd397071f5224

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



rollix-page-120-curve.webp | SHA-256: 8db3c72c4d15922ba22691da5940bde446bb831dd20545f70889fbe8d4f5f9e2

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID YZWCU54IY4C7RH6ON7PV3E7TIY	SOURCE DOCUMENT ROLLIX-CATALOGUE-SLEWING-RINGS-2024-07
SOURCE FILE ROLLIX.pdf	SOURCE LOCATION PDF page 120 Printed page 120
VERIFICATION Level 3 - MERYDOM Engineering Verified	REVIEWED BY MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1

Confirm the exact model designation and all installation-envelope dimensions.
- 2

Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3

Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4

Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5

Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6

Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/rollix/46-0944-00/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.