

Factory-Verified Replacement

MERYDOM RKS.060.20.0544

Certified for interchange with SKF RKS.060.20.0544. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

RKS.060.20.0544

REFERENCE

SKF RKS.060.20.0544

SERIES

SKF_BALL_MEDIUM_UNGEARED Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

616 mm

OVERALL ID

472 mm


OVERALL HEIGHT

mm

GEAR

Sem engrenagem

Published Technical Drawing



skf-p076-outline-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	RKS.060.20.0544
Certified interchangeable with	SKF RKS.060.20.0544
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	PZANATEBEO725JJLY5O3AEBKUU
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	SKF
Reference series	SKF_BALL_MEDIUM_UNGEARED Series
Reference model	RKS.060.20.0544
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Sem engrenagem
DIMENSION	
Raceway diameter (dm)	544 mm
Overall outside diameter (D)	616 mm
SKF catalogue dimension D1 (D1)	545,5 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (d)	472 mm
SKF catalogue dimension d1 (d1)	542,5 mm
Mass (Mass)	37 kg
MOUNTING	
Outer ring bolt circle (Je)	590 mm
Outer ring mounting-hole specification (Ke)	13,5 mm
Outer ring mounting-hole count (Ne)	32 count
Inner ring bolt circle (Ji)	498 mm
Inner ring mounting-hole specification (Ki)	13,5 mm
Inner ring mounting-hole count (Ni)	32 count
PERFORMANCE	
Basic dynamic axial load rating (C)	233 kN
Basic static axial load rating (C0)	1.350 kN
PERFORMANCE RATINGS	
Basic Dynamic Axial	233 kN
Basic Static Axial	1.350 kN
MOUNTING INTERFACES	
Outer ring mounting	32 holes - 13,5
Inner ring mounting	32 holes - 13,5
GEAR INTERFACE	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

GEAR INTERFACE (CONTINUED)	
Integral gear	Not applicable - ungeared bearing
SOURCE TRACEABILITY	
Source document code	SKF_SLEWING_BEARINGS_PUB_BU_P2_06115_3_EN_2019_09
Source file	SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf
PDF page	76
Printed page	76
Source language	EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	skf-p077-load-curve.webp SHA-256: 56fe67eebc133e0d2947b156b32493b08dc465c14a54fee3aae35933805b4165
Outline Drawing	skf-p076-outline-drawing.webp SHA-256: af39ce87b8bc13a48e6ccfe3361fdb574237c0c3bce45175d75d86edf940253

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



skf-p077-load-curve.webp | SHA-256: 56fe67eebc133e0d2947b156b32493b08dc465c14a54fee3aae35933805b4165

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID

PZANATEBEO725JJLY5O3AEBKUU

SOURCE FILE

SKF_Slewing_Bearings_PUB_BU_P2_06115_3_EN_2019-09.pdf

VERIFICATION

Level 3 - MERYDOM Engineering
Verified

SOURCE DOCUMENT

SKF_SLEWING BEARINGS_PUB_BU_P2_06115_3_EN_2019_09

SOURCE LOCATION

PDF page 76 | Printed page 76

REVIEWED BY

MERYDOM Engineering Department

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page: <https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/skf/rks-060-20-0544/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.