

Factory-Verified Replacement

MERYDOM E.712.2.25.12.D.6

Certified for interchange with Torriani Gianni E.712.2.25.12.D.6. This document consolidates the public product record, complete published specifications, technical media, source traceability and engineering confirmation notes.

LEVEL 3 - MERYDOM ENGINEERING VERIFIED

Reviewed by MERYDOM Engineering Department. Final application approval must confirm loads, duty cycle, mounting rigidity, bolt capacity, lubrication and operating conditions.

MERYDOM MODEL

E.712.2.25.12.D.6

REFERENCE

Torriani Gianni E.712.2.25.12.D.6

SERIES

E_2_20_22_25_D Series

STRUCTURE

Esferas de contato de quatro pontos

OVERALL OD

712 mm

OVERALL ID

470 mm


OVERALL HEIGHT

98 mm

GEAR

Engrenagem externa

Published Technical Drawing



e_2_20_22_25_d-drawing.webp

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

MERYDOM CERTIFIED PRODUCT	
Product brand	MERYDOM
MERYDOM model	E.712.2.25.12.D.6
Certified interchangeable with	Torriani Gianni E.712.2.25.12.D.6
Verification status	Level 3 - MERYDOM Engineering Verified
Reviewed by	MERYDOM Engineering Department
Public record UID	253SJMYE4J5Z44QCERZUGLY6MZ
MATERIALS	
Configurable ring material options	42CrMo / 50Mn
Seal material	NBR - Nitrile rubber
Configurable spacer material options	Engineering nylon / Brass
IDENTIFICATION	
Reference brand	Torriani Gianni
Reference series	E_2_20_22_25_D Series
Reference model	E.712.2.25.12.D.6
Bearing structure	Esferas de contato de quatro pontos
Gear arrangement	Engrenagem externa
DIMENSION	
Overall outside diameter (Da)	712 mm
Torriani catalogue dimension U (U)	670 mm
Torriani catalogue dimension O (O)	577 mm

Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

DIMENSION (CONTINUED)	
Overall inside diameter (Di)	470 mm
Torriani catalogue dimension Ha (Ha)	75 mm
Torriani catalogue dimension Hb (Hb)	88 mm
Overall height (H)	98 mm
Mass (Kg)	103 kg
MOUNTING	
Outer ring bolt circle (La)	640 mm
Outer ring mounting-hole count (na)	24
Outer ring mounting-hole specification (da)	17 mm
Inner ring bolt circle (Li)	508 mm
Inner ring mounting-hole count (ni)	24
Inner ring mounting-hole specification (di)	17 mm
GEAR	
Gear pitch diameter (P)	696 mm
Gear module (m)	8 mm
Gear tooth count (z)	87
PERFORMANCE	
Normal tooth force (Fz_normal)	41 kN
Maximum tooth force (Fz_max)	82 kN
PERFORMANCE RATINGS	


Complete Product Data

All values below are generated from the current public verified replacement record. Source values are retained and metric references are shown where available.

PERFORMANCE RATINGS (CONTINUED)	
Rating Tooth Force Normal	41 kN Not simultaneous with other listed dynamic ratings
Rating Tooth Force Max	82 kN Not simultaneous with other listed dynamic ratings
MOUNTING INTERFACES	
Outer ring mounting	24 holes - da 17 mm
Inner ring mounting	24 holes - di 17 mm
GEAR INTERFACE	
Pitch system	module
Module reference	8 mm
Number of teeth	87
SOURCE TRACEABILITY	
Source document code	TORRIANI_GIANNI_BALL_BEARINGS_CATALOG
Source file	catalogo-torriani-cuscinetti-a-sfere.pdf
PDF page	25
Printed page	25
Source language	IT-EN
Original unit system	Metric
PUBLISHED TECHNICAL MEDIA	
Load Curve Chart	e_2_20_22_25_d-static-load-curve.webp SHA-256: 168c0de0d6480888146a14da7726693e41f1694e1108110070b74bb1b81330f2
Outline Drawing	e_2_20_22_25_d-drawing.webp SHA-256: 8a0b8d9737e1e00ce011f1d4807a875c21d76a93e09826f00cbc218e71eff044

Published Load / Performance Chart

Use the published chart as a preliminary selection aid only. The model legend, curve family and source document must be reviewed together with the operating load case.



e_2_20_22_25_d-static-load-curve.webp | SHA-256:
168c0de0d6480888146a14da7726693e41f1694e1108110070b74bb1b81330f2

Engineering note: final approval must also consider mounting rigidity, bolt capacity, duty cycle, lubrication, temperature, environment and installation conditions.

Source and Verification Traceability

PUBLIC RECORD UID**253SJMYE4J5Z44QCERZUGLY6MZ****SOURCE FILE****catalogo-torriani-cuscinetti-a-sfere
.pdf****VERIFICATION****Level 3 - MERYDOM Engineering
Verified****SOURCE DOCUMENT****TORRIANI_GIANNI_BALL_BEARINGS_CATALO
G****SOURCE LOCATION****PDF page 25 | Printed page 25****REVIEWED BY****MERYDOM Engineering Department**

Engineering Confirmation Boundary

- 1 Confirm the exact model designation and all installation-envelope dimensions.
- 2 Confirm mounting-hole quantity, bolt circle, hole specification, bolt grade and preload.
- 3 Confirm gear arrangement, pitch system, tooth count, backlash and mating-pinion data.
- 4 Confirm axial, radial and moment loads, load combinations, duty cycle and required life.
- 5 Confirm support flatness and stiffness, lubrication, sealing, temperature and environment.
- 6 Final drawing revision, manufacturing tolerances and documentation package are confirmed with the quotation.

Request Price, Delivery and Final Engineering Confirmation

Email: jovi@merydom.com | Email: andi@merydom.com | WhatsApp: +86 17705201170

Product page:

<https://rotnex.com/pt/produtos/rolamentos-de-giro-de-substituicao/torriani-gianni/e-712-2-25-12-d-6/>

Trademark and legal notice: referenced brand and model names are used only for identification and cross-reference. MERYDOM is an independent manufacturer and is not affiliated with or endorsed by the referenced brand unless expressly stated.